

Wi-Fi CERTIFIED® Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA91325

Product Info

Date of Certification May 29, 2020

Company Vantiva

Product Name FGA5330

Product Model Variant 2020-05-29 (WFA91325 - 9724924)

Model Number FGA5330TCH

Category Routers

Sub-category Access Point for Home or Small Office (Wireless Router)

Summary of Certifications

CLASSIFICATION CERTIFICATION

Network management WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2018-04 WPA3[™]-Enterprise 2018-04 WPA3[™]-Personal 2019-08

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Spectrum & Regulatory
Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



Wi-Fi CERTIFIED® Certificate

Certification ID: WFA91325



Role: Access Point Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Linux, version:4.1.52

Wi-Fi Component Firmware

19.4.0279

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz160 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d

WMM®

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2018-04

WPA3™-Enterprise 2018-04

EAP methods

WPA3™-Personal 2019-08

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED 6®

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx



Wi-Fi CERTIFIED® Certificate

Certification ID: WFA91325



Role: Access Point Page 3 of 3

Wi-Fi CERTIFIED 6® (continued)

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx