

Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA110882

Product Info

Date of Certification March 29, 2021

Company Samsung Electronics

Product Name S5E9815_ERD

Product Model Variant N/A

Model Number REV00A

Category Phones

Sub-category Smartphone

Summary of Certifications

CLASSIFICATION CERTIFICATION

Network management WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-02

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Spectrum & Regulatory
Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA110882



Role: Station Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Android 11

Wi-Fi Component Firmware

J|1707|2021-03-09

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

WPA2™-Enterprise 2018-04 (continued)

EAP TTLS

PEAPv0

PEAPv1

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

Spectrum & Regulatory

Protected Management Frames

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods

EAP TLS

EAP TTLS

PEAPv0

PEAPv1

Server Certificate Validation

WMM®

802.11h

Max Throughput

WPA3™-Personal 2020-02

Wi-Fi Agile Multiband™

WPA2™-Enterprise 2018-04

EAP methods EAP TLS

ANQP

ANQP-based Neighbor report

BTM Query

Cellular Data capable



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA110882



Role: Station Page 3 of 3

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

HE NDP

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode control field

Operating mode subfield in A-Control field

Operating mode indication

SU beamformee

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8 Rx

MCS 8-9 Rx

Short Guard Interval

STBC

Wi-Fi CERTIFIED™ ac (continued)

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC

A-MPDU Tx

HT Duplicate Mode

OBSS on Extension Channel

Power Management

Short Guard Interval