



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA110882

Product Info

Date of Certification	March 29, 2021
Company	Samsung Electronics
Product Name	S5E9815_ERD
Product Model Variant	N/A
Model Number	REV00A
Category	Phones
Sub-category	Smartphone

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-02
Spectrum & Regulatory Features	Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA110882



Role: Station

Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Android 11

Wi-Fi Component Firmware

J|1707|2021-03-09

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11h

WMM®

Max Throughput

WPA2™-Enterprise 2018-04

EAP methods
EAP TLS

WPA2™-Enterprise 2018-04 (continued)

EAP TTLS
PEAPv0
PEAPv1

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods
EAP TLS
EAP TTLS
PEAPv0
PEAPv1
Server Certificate Validation

WPA3™-Personal 2020-02

Wi-Fi Agile Multiband™

ANQP
ANQP-based Neighbor report
BTM Query
Cellular Data capable



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA110882



Role: Station

Page 3 of 3

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Beamforming sounding
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
HE NDP
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
Operating mode control field
Operating mode subfield in A-Control field
Operating mode indication
SU beamformee
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
MCS 8 Rx
MCS 8-9 Rx
Short Guard Interval
STBC
LDPC Tx

Wi-Fi CERTIFIED™ ac (continued)

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC
A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel
Power Management
Short Guard Interval