



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

## **Certification ID: WFA111292**

### **Product Info**

Date of Certification April 16, 2021

**Company** Huawei Technologies Co., Ltd.

Product Name Optical Network Terminal

Product Model Variant HG8247X6-8N

Model Number HG8247X6-8N

**Category** Routers

Sub-category Cable, DSL or Other Broadband Gateway (Integrated Home Access

Device)

## **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Alternative topologies Wi-Fi EasyMesh™

Network management WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2020-02 WPA3<sup>™</sup>-Personal 2020-02

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Spectrum & Regulatory
Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



**Certification ID: WFA111292** 



Role: Access Point	Page 2 of 4		
Wi-Fi Components Wi-Fi Component Operating System	RF Architecture		
Linux Wi-Fi Component Firmware V5	Bands Supported 2.4 GHz 5 GHz	Transmit (Tx) 4 4	Receive (Rx) 4 4
Certifications			
2.4 GHz Spectrum Capabilities  20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz	WMM®-Power Sav	ve (continued)	
5 GHz Spectrum Capabilities  20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	WPA2™-Enterprise 2018-04  EAP methods		
	WPA2™-Personal 2021-01  WPA3™-Enterprise 2020-02		
Protected Management Frames	EAP methods		
Spectrum & Regulatory	WPA3™-Personal 2020-02		
802.11d 802.11h	Wi-Fi Agile Multib	and™	
WMM®-Power Save  Legacy Power Save	Wi-Fi CERTIFIED  4 antenna support  A-MPDU with A-MSDU  Basic Trigger frame in H  Beamforming sounding		



**Certification ID: WFA111292** 



Role: Access Point Page 3 of 4

### Wi-Fi CERTIFIED 6® (continued)

**BSRP** Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

**UL OFDMA** 

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

**Short Guard Interval** 

STBC

### Wi-Fi CERTIFIED™ ac (continued)

SU beamformer

#### Wi-Fi CERTIFIED™ b

#### Wi-Fi CERTIFIED™ g

#### Wi-Fi CERTIFIED™ n

**OBSS on Extension Channel** 

Short Guard Interval

STBC

A-MPDU Tx

### Wi-Fi Protected Setup™

PIN

Pushbutton



**Certification ID: WFA111292** 



Role: Controller	Page 4 of 4
Wi-Fi Components	
Wi-Fi Component Operating System	
Linux	
Certifications	
Wi-Fi EasyMesh™	