



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA111351

Product Info

Date of Certification March 24, 2021

Company Extreme Networks

Product Name AP460S12C

Product Model Variant 2020-06-29 (WFA100729 - 11313149)

Model Number AP460S12C

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 2

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-02

WPA™-Enterprise WPA™-Personal





Certification ID: WFA111351

Summary of Certifications (continued)

Page 2 of 4

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory

Spectrum & Regulatory

Features



Certification ID: WFA111351



Role: Access Point		Pa	age 3 of 4	
Vi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Proprietary / Other, version:10.3r2, description:HiveOS	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware	2.4 GHz	2	2	
HiveOS 10.3r2	5 GHz	4	4	
Certifications				
2.4 GHz Spectrum Capabilities	WMM®-Power Save	WMM®-Power Save		
20 MHz Channel Width in 2.4 GHz	Legacy Power Save Unschedule auto PS			
5 GHz Spectrum Capabilities	IMPACIM Futurein	- 0040 04		
20 MHz Channel Width in 5 GHz	WPA2™-Enterprise 2018-04			
40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	EAP methods			
160 MHz Channel Width in 5 GHz	WPA2™-Personal 2	2021-01		
Passpoint® Release 2	WPA3™-Enterprise	WPA3™-Enterprise 2020-02		
Online Sign Up and Policy provisioning	EAP methods	EAP methods		
Protected Management Frames	WPA3™-Personal 2	WPA3™-Personal 2020-02		
Spectrum & Regulatory	WPA™-Enterprise	WPA™-Enterprise		
802.11d 802.11h	WPA™-Personal			
002.1111	Wi-Fi Agile Multiba	nd™		
WMM®	Automatically populate B	Automatically populate BSS Transition candidate list		







Role: Access Point Page 4 of 4

Wi-Fi Agile Multiband™ (continued)

Fast Transition OTA on WPA2-Enterprise Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6®

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating Mode indication

SU beamformer

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

Wi-Fi CERTIFIED™ ac (continued)

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

HT Duplicate Mode

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx