Wi-Fi CERTIFIED® Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA111375

Product Info

Date of Certification	May 3, 2021
Company	MediaTek Inc.
Product Name	Toucan
Product Model Variant	NA
Model Number	MT7922, RZ616
Category	Other
Sub-category	Reference Design

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Alternative topologies	Wi-Fi Direct®
Network management	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-02 Wi-Fi Enhanced Open™ 2021-01
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Spectrum & Regulatory Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b

CLASSIFICATION	CERTIFICATION
Wi-Fi (MAC/PHY)	Wi-Fi CERTIFIED™ g
	Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED® Certificate

Certification ID: WFA111375

Wi-Fi Components

Wi-Fi Component Operating System

Windows 10

Wi-Fi Component Firmware

Windows

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2
6 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz
40 MHz Channel Width in 6 GHz
80 MHz Channel Width in 6 GHz
160 MHz Channel Width in 6 GHz

Protected Management Frames

Spectrum & Regulatory

Spectrum & Regulatory (continued)

802.11h

WMM®

WMM®-Power Save

WPA2™-Enterprise 2018-04

EAP methods
    EAP TLS
    PEAPv0

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods
    EAP TLS
    PEAPv0
Server Certificate Validation

WPA3™-Personal 2020-02

Wi-Fi Agile Multiband™

Beacon Report Measurement Passive Mode

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode subfield in A-Control field
SU beamformee
UL OFDMA
Wi-Fi 6E

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support
RTS with BW Signaling
A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
MCS 8-9 Rx

Wi-Fi CERTIFIED™ ac (continued)

Short Guard Interval
LDPC Tx
SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel
Short Guard Interval

Wi-Fi Direct®

Wi-Fi Enhanced Open™ 2021-01

Wi-Fi Protected Setup™

PIN
Pushbutton