



Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs



Certification ID: WFA112024

Product Info

Date of Certification	May 20, 2021
Company	Quanta Computer Inc.
Product Name	QTAD53
Product Model Variant	N/A
Model Number	QTAD53
Category	Routers
Sub-category	Mobile Access Point

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM®
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2020-02 WPA™-Personal



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA112024



Role: Access Point

Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

OpenWRT

Wi-Fi Component Firmware

gem-mp-1907-mp1.V1.12

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2020-02

WPA™-Personal

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU

Wi-Fi CERTIFIED 6® (continued)

BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-RTS Trigger frame
OM subfield in A-Control field
Operating Mode indication
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA112024



Role: Access Point

Page 3 of 3

Wi-Fi CERTIFIED™ ac (continued)

Extended 5 GHz Channel Support
RTS with BW Signaling
A-MPDU with A-MSDU
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
DL MU-MIMO
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel
Short Guard Interval
STBC
A-MPDU Tx

Wi-Fi Protected Setup™

PIN
Pushbutton