



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA103759

Product Info

Date of Certification May 18, 2021

Company MediaTek Inc.

Product Name MT7921K

Product Model Variant WPA3 update

Model Number MT7921K, RZ608

Category Other

Sub-category Reference Design

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Direct®

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-02

WPA™-Enterprise





Certification ID: WFA103759

Summary of Certifications (continued)

Page 2 of 4

CLASSIFICATION

CERTIFICATION

Security

WPA™-Personal

Spectrum & Regulatory

Spectrum & Regulatory

Features





Certification ID: WFA103759

Role: Station		P	age 3 of 4	
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Windows 10 Wi-Fi Component Firmware Windows	Bands Supported	Transmit (Tx)	Receive (Rx)	
	2.4 GHz	2	2	
vvindows	5 GHz	2	2	
	6 GHz	2	2	
Certifications				
2.4 GHz Spectrum Capabilities	WMM®	WMM®		
20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz	WMM®-Power Save			
	WPA2™-Enterprise 2018-04			
5 GHz Spectrum Capabilities				
20 MHz Channel Width in 5 GHz	EAP methods EAP TLS			
40 MHz Channel Width in 5 GHz	PEAPv0			
80 MHz Channel Width in 5 GHz	WPA2™-Personal	2021-01		
6 GHz Spectrum Capabilities	_			
20 MHz Channel Width in 6 GHz	WPA3™-Enterpris	e 2020-02		
40 MHz Channel Width in 6 GHz	EAP methods EAP TLS			
80 MHz Channel Width in 6 GHz	PEAPv0			
Protected Management Frames	Server Certificate Valida	tion		
-	WPA3™-Personal	2020-02 		
Spectrum & Regulatory	WDA IN Entorprise			
802.11h	WPA™-Enterprise			
	WPA™-Personal			





Certification ID: WFA103759

Role: Station Page 4 of 4

Wi-Fi Agile Multiband™

Beacon Report Measurement Passive Mode

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL Mu PPDU multi-tone

DL MU-MIMO

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

OM subfield in A-Control field

SU beamformee

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi 6E

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

Wi-Fi CERTIFIED™ ac (continued)

MCS 8-9 Rx

Short Guard Interval

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode

OBSS on Extension Channel

Short Guard Interval

Wi-Fi Direct®

Wi-Fi Protected Setup™

PIN

Pushbutton