Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA114311

Product Info

Date of Certification	January 27, 2022
Company	NEC Corporation
Product Name	WX5400HP
Product Model Variant	WX5400HP
Model Number	WX5400HP
Category	Routers
Sub-category	Access Point for Home or Small Office (Wireless Router)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2020-02 WPA™-Personal

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA114311

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

0.1.6

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

0.1.6

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
5 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WMM®-Power Save

Legacy Power Save
Unschedule auto PS

WPA2™-Personal 2021-01

WPA3™-Personal 2020-02

WPA™-Personal

Wi-Fi Agile Multiband™

Cellular Data aware

Wi-Fi CERTIFIED 6®

4 antenna support
A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA114311

Wi-Fi CERTIFIED 6® (continued)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating Mode indication

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx