



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA114424

Product Info

Date of Certification	September 22, 2021
Company	SYNCLAYER INC.
Product Name	GPON Terminal
Product Model Variant	SGP210W
Model Number	SGP210W
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ f
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™
Security	Protected Management Frames WPA2 [™] -Enterprise 2018-04 WPA2 [™] -Personal 2021-01 WPA3 [™] -Enterprise 2020-02 WPA3 [™] -Personal 2020-02



Certification ID: WFA114424



Summary of Certifications (continued)Page 2 of 5CLASSIFICATIONCERTIFICATIONSpectrum & Regulatory
FeaturesSpectrum & Regulatory

This certificate was downloaded on 2024-04-26 at 23:55:53 UTC



Wi-Fi CERTIFIED[™] Certificate

Certification ID: WFA114424



Role: Access Point	Pa	Page 3 of 5	
Wi-Fi Components			
Wi-Fi Component Operating System Linux Wi-Fi Component Firmware V5	RF Architecture Bands Supported 2.4 GHz 5 GHz	Transmit (Tx) 4 4	Receive (Rx) 4 4
Certifications			
2.4 GHz Spectrum Capabilities	WMM®-Power Save (continued)		
20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz	Unschedule auto PS		
5 GHz Spectrum Capabilities 20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz	WPA2 [™] -Enterpris EAP methods WPA2 [™] -Personal		
80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	WPA3™-Enterpris		
Protected Management Frames	EAP methods		
Spectrum & Regulatory	WPA3™-Personal 2020-02		
802.11d 802.11h	Wi-Fi Agile Multiband™		
WMM® WMM®-Power Save Legacy Power Save	4 antenna support A-MPDU with A-MSDU Basic Trigger frame in H Beamforming sounding		



Certification ID: WFA114424



Page 4 of 5

Role: Access Point

Wi-Fi CERTIFIED 6® (continued)

BSRP Trigger frame Compressed Block Ack Rx (buffer size 256) Compressed Block Ack Tx (buffer size 256) DL MU-MIMO DL OFDMA Individual Target Wake Time LDPC Rx LDPC Tx MCS 8-9 Rx MCS 8-9 Tx MU EDCA Parameter Set element MU-BAR Trigger frame MU-RTS Trigger frame M-BSSID Operating Mode indication SU beamformer **TXOP RTS Threshold** UL OFDMA

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel Short Guard Interval STBC A-MPDU Tx

Wi-Fi Protected Setup™

PIN

Pushbutton

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED[™] ac

RTS with BW Signaling Extended 5 GHz Channel Support A-MPDU with A-MSDU DL MU-MIMO LDPC Rx LDPC Tx MCS 8-9 Rx Short Guard Interval STBC SU beamformer

Wi-Fi CERTIFIED™ b



Certification ID: WFA114424



Role: Controller

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™