

Wi-Fi CERTIFIED® Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA100148

Product Info

Date of Certification November 23, 2021

Company MediaTek Inc.

Product Name MT7921

Product Model Variant P2P version

Model Number MT7921

Category Other

Sub-category Reference Design

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Alternative topologies Wi-Fi Direct®

Network management WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2018-04 WPA3[™]-Enterprise 2018-04 WPA3[™]-Personal 2019-08

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Spectrum & Regulatory
Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



Wi-Fi CERTIFIED® Certificate

Certification ID: WFA100148



Role: Station Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Windows 10

Wi-Fi Component Firmware

Windows 10

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11h

WMM®

WPA2™-Enterprise 2018-04

EAP methods
EAP TLS
PEAPv0

WPA2™-Personal 2018-04

WPA3™-Enterprise 2018-04

EAP methods
EAP TLS
PEAPv0

WPA3™-Personal 2019-08

Wi-Fi Agile Multiband™

Beacon Report Measurement Passive Mode

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

BSRP Trigger frame Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx



Wi-Fi CERTIFIED® Certificate

Certification ID: WFA100148



Role: Station Page 3 of 3

Wi-Fi CERTIFIED 6® (continued)

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode control field

Operating mode subfield in A-Control field

SU beamformee

UL OFDMA

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Power Management

Short Guard Interval

Wi-Fi Direct®

Wi-Fi Protected Setup™

PIN

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode