



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA101064

Product Info

Date of Certification December 1, 2021

Company Intel

Product Name Intel® Wi-Fi 6E AX210 (Gig+)

Product Model Variant QoS update

Model Number AX210

Category Computers & Accessories

Sub-category Internal Adapter

Summary of Certifications

CLASSIFICATION CERTIFICATION

Applications & Services Wi-Fi Location™ R1

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2021-01

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi QoS Management™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-12





Certification ID: WFA101064

Summary of Certifications (continued)		Page 2 of 5
CLASSIFICATION	CERTIFICATION	
Security	WPA™-Enterprise WPA™-Personal	
Spectrum & Regulatory Features	Spectrum & Regulatory	



Certification ID: WFA101064



Role: Station Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

9.5.1;commit:9653feaf;date:2021-10-21T15: 33:52-07:00

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2
6 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz 40 MHz Channel Width in 6 GHz 80 MHz Channel Width in 6 GHz 160 MHz Channel Width in 6 GHz

Protected Management Frames

Spectrum & Regulatory

Spectrum & Regulatory (continued)

802.11h

WMM®

Max Throughput

WMM®-Power Save

Legacy Power Save Unschedule auto PS

WPA2[™]-Enterprise 2018-04

EAP TLS
EAP TTLS
PEAPv0
PEAPv1

EAP methods

WPA2™-Personal 2021-01



Certification ID: WFA101064



Role: Station Page 4 of 5

WPA3™-Enterprise 2020-02

EAP methods

EAP TLS

EAP TTLS

PEAPv0

PEAPv1

192-bit security

192-bit security RSA 3K with the

TLS_DHE_RSA_WITH_AES_256_GCM_SHA384 cipher suite

192-bit security RSA 3K with the

TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 cipher suite

Fast Transition OTA on WPA3-Enterprise

Fast Transition OTA on WPA3-Enterprise transition mode

Server Certificate Validation

WPA3™-Personal 2020-12

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

ANQP

ANQP-based Neighbor report

Beacon Report Measurement Active Mode

Beacon Report Measurement Passive Mode

BTM Query

Cellular Data capable

Fast Transition OTA on WPA2-Personal

Fast Transition OTA on WPA2-Enterprise

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Wi-Fi CERTIFIED 6® (continued)

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL Mu PPDU multi-tone

DL MU-MIMO

HE NDP

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

OM Control field Tx

OM subfield in A-Control field

Operating Mode indication

SU beamformee

SU-MIMO

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi 6E

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx





Certification ID: WFA101064

Role: Station Page 5 of 5

Wi-Fi CERTIFIED™ ac (continued)

Short Guard Interval

STBC

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC

A-MPDU Tx

OBSS on Extension Channel

Power Management

Short Guard Interval

Wi-Fi Enhanced Open™ 2021-01

Wi-Fi Location™ R1

Fine Timing Measurement 2017

Wi-Fi QoS Management™

Default DSCP to UP mapping

DSCP QoS Map

DSCP Policy

Mirrored Stream Classification Service

MSCS setup at association

Stream Classification Service