

Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA118900

Product Info

Date of Certification March 17, 2022

Company Huawei Technologies Co., Ltd.

Product Name Wireless LAN Access Point

Product Model Variant AirEngine5761-12

Model Number AirEngine5761-12

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-02

Spectrum & Regulatory

Features

Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA118900



Role: Access Point	Page 2 of 3
Wi-Fi Components	
Wi-Fi Component Operating System	RF Architecture
Linux	Bands Supported Transmit (Tx) Receive (Rx)
Wi-Fi Component Firmware	2.4 GHz 2 2
Ver.A	5 GHz 2 2
Certifications	
2.4 GHz Spectrum Capabilities	WPA2™-Enterprise 2018-04 (continued)
20 MHz Channel Width in 2.4 GHz	EAP methods
40 MHz Channel Width in 2.4 GHz	
5 GHz Spectrum Capabilities	WPA2™-Personal 2021-01
20 MHz Channel Width in 5 GHz	WPA3™-Enterprise 2020-02
40 MHz Channel Width in 5 GHz	EAP methods
80 MHz Channel Width in 5 GHz	192-bit security
Protected Management Frames	WPA3™-Personal 2020-02
Spectrum & Regulatory	Wi-Fi Agile Multiband™
802.11d	Automatically populate BSS Transition candidate list
802.11h	Cellular Data aware
WMM®	Wi-Fi CERTIFIED 6®
WMM®-Power Save	A-MPDU with A-MSDU
WPA2™-Enterprise 2018-04	Basic Trigger frame in HE MU PPDU Beamforming sounding
WI AZ -Litterprise 2010-04	BSRP Trigger frame



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA118900



Role: Access Point Page 3 of 3

Wi-Fi CERTIFIED 6® (continued)

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx