



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

### **Certification ID: WFA118925**

#### **Product Info**

Date of Certification April 25, 2022

Company FCNT LLC

Product Name F-51A

Product Model Variant OS Version UP\_S

Model Number F-51A

**Category** Phones

**Sub-category** Smartphone

### **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 3

Alternative topologies Wi-Fi Direct®

**Applications** Miracast®

Network management WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2020-02 WPA3<sup>™</sup>-Personal 2020-12 Wi-Fi Enhanced Open<sup>™</sup> 2021-01

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ b



**Certification ID: WFA118925** 



Summary of Certifications (continued)		Page 2 of 7
CLASSIFICATION	CERTIFICATION	
Wi-Fi (MAC/PHY)	Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n	



**Certification ID: WFA118925** 



Role: Access Point Page 3 of 7

Wi-Fi Components

Wi-Fi Component Operating System

Android Version 12

Wi-Fi Component Firmware

VXXR0XX

**WMM®** 

**RF Architecture** 

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

20 MHZ Channel Width in 2.4 GHZ

**Protected Management Frames** 

\_\_\_\_\_

WPA2™-Personal 2021-01

WPA3™-Personal 2020-12

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

Operating mode indication

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

Short Guard Interval

STBC

A-MPDU Tx

Wi-Fi Enhanced Open™ 2021-01



**Certification ID: WFA118925** 



Role: Station Page 4 of 7

#### Wi-Fi Components

Wi-Fi Component Operating System

Android Version 12

Wi-Fi Component Firmware

VXXR0XX

#### **RF Architecture**

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

#### Certifications

#### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

#### 5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

#### Passpoint® Release 3

Display and input method

Display of HS2.0 indication

Operating Class Indication

Network Icon support

Network Information in network selection

Online Sign Up and Policy provisioning

Fast Transition OTA on WPA2-Enterprise

Online Sign Up using single SSID

Venue Information

Terms and Conditions

Roaming Consortium Selection

#### **Protected Management Frames**

#### **WMM®**

#### WMM®-Power Save

Unschedule auto PS

### WPA2™-Enterprise 2018-04

EAP methods

EAP AKA

**EAP AKA Prime** 

EAP SIM

EAP TLS

**EAP TTLS** 

PEAPv0

PEAPv1

#### WPA2™-Personal 2021-01

#### WPA3™-Enterprise 2020-02

EAP methods

EAP AKA

EAP AKA Prime

EAP SIM



**Certification ID: WFA118925** 



Role: Station Page 5 of 7

#### WPA3™-Enterprise 2020-02 (continued)

**EAP TLS** 

**EAP TTLS** 

PEAPv0

PEAPv1

192-bit security

192-bit security RSA 3K with the

TLS\_ECDHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384

cipher suite

Server Certificate Validation

#### WPA3™-Personal 2020-12

#### Wi-Fi Agile Multiband™

**ANQP** 

ANQP-based Neighbor report

Beacon Report Measurement Active Mode

Beacon Report Measurement Passive Mode

BTM Query

Cellular Data capable

Fast Transition OTA on WPA2-Personal

Fast Transition OTA on WPA2-Enterprise

#### Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

HE NDP

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

#### Wi-Fi CERTIFIED 6® (continued)

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode control field

Operating mode subfield in A-Control field

Operating mode indication

SU beamformee

SU-MIMO

**UL OFDMA** 

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

STBC

LDPC Tx

SU beamformee

#### Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

#### Wi-Fi CERTIFIED™ n

STBC



**Certification ID: WFA118925** 



Role: Station

Wi-Fi CERTIFIED™ n (continued)

A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval

Wi-Fi Direct®

Wi-Fi Enhanced Open™ 2021-01



**Certification ID: WFA118925** 



Role: Source	Page 7 of 7		
Wi-Fi Components			
Wi-Fi Component Operating System	RF Architecture		
Android Version 12	Bands Supported	Transmit (Tx)	Receive (Rx)
Wi-Fi Component Firmware VXXR0XX	2.4 GHz	2	2
V/V/(\(\text{\tin}\ext{\tin}\tint{\text{\text{\tin}\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\texict{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\tin}\tint{\text{\text{\text{\text{\tinit}\text{\text{\text{\tinit}}\tint{\text{\text{\text{\text{\ti}\tint{\text{\text{\text{\tinit}\tint{\text{\text{\text{\text{\ti}\tint{\text{\tinit}\tittt{\text{\ti}\tint{\text{\tinit}\tittt{\tinithtet{\text{\tinit}\tittt{\tinithtet{\tiin\tint{\titt{\tinit}\tittt{\ti}\tittt{\tinitt{\tiin\tinit{\tii\titt{\tii}\	5 GHz	2	2
Certifications			
Miracast®			
HDCP Encryption			