



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA117098

Product Info

Date of Certification	May 12, 2022
Company	Harman International Industries, Inc.
Product Name	MGU22H
Product Model Variant	MGU22 H
Model Number	MGU22H
Category	Other
Sub-category	In-vehicle Network

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Direct®
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2020-12



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA117098



Role: Access Point

Page 2 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

w9098o-V1, RF878X, FP68_LINUX, 17.68.1.p109.12

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

Max Throughput

WPA2™-Personal 2021-01

WPA3™-Personal 2020-12

Wi-Fi CERTIFIED 6™

A-MPDU with A-MSDU
LDPC Rx

Wi-Fi CERTIFIED 6™ (continued)

LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
SU beamformer
TXOP RTS Threshold

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA117098



Role: Access Point

Page 3 of 5

Wi-Fi CERTIFIED™ n

HT Duplicate Mode
OBSS on Extension Channel
Short Guard Interval
STBC
A-MPDU Tx



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA117098



Role: Station

Page 4 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

w9098o-V1, RF878X, FP68_LINUX, 17.68.1.p109.12

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

Max Throughput

WPA2™-Personal 2021-01

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

ANQP
Beacon Report Measurement Active Mode

Wi-Fi Agile Multiband™ (continued)

Beacon Report Measurement Passive Mode
Cellular Data capable

Wi-Fi CERTIFIED 6™

A-MPDU with A-MSDU
BSRP Trigger frame
DL Mu PPDU multi-tone
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
OM Control field Tx
OM subfield in A-Control field
SU beamformee
UL OFDMA
UL TB PPDU multi-tone



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA117098



Role: Station

Page 5 of 5

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
MCS 8-9 Rx
Short Guard Interval
STBC
LDPC Tx
SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC
A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel
Short Guard Interval

Wi-Fi Direct®

Wi-Fi Protected Setup™

PIN
Pushbutton