



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA119716

Product Info

Date of Certification May 17, 2022

Company Huawei Technologies Co., Ltd.

Product Name GPON Terminal

Product Model Variant OptiXstar EG8141XR-10

Model Number OptiXstar EG8141XR-10

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-02







Role: Access Point Page 2 of 4

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

V5

RF Architecture

2.4 GHz

Bands Supported Transmit (Tx) Receive (Rx)

2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods

WPA3™-Personal 2020-02

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Protected Management Frames

WMM®

WMM®-Power Save

Legacy Power Save Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx



Certification ID: WFA119716



Role: Access Point Page 3 of 4

Wi-Fi CERTIFIED 6® (continued)

MCS 10-11 Tx

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating Mode indication

SU beamformer

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx

Wi-Fi EasyMesh™

Wi-Fi EasyMesh™ (continued)

Backhaul Link

Backhaul in 2.4 GHz

Backhaul in 5 GHz low band

Backhaul in 5 GHz high band

Backhaul over Ethernet

Fronthaul Access Point

Fronthaul in 2.4 GHz

Fronthaul in 5 GHz low band

Fronthaul in 5 GHz high band

Client Capability Query

Unassociated STA Link Metrics Reporting

Backhaul onboarding with Pushbutton

Coordinated CAC

Traffic separation

Wi-Fi Protected Setup™

PIN

Pushbutton





Certification ID: WFA119716

Role: Controller

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™