Wi-Fi CERTIFIED® Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA119624

Product Info

Date of Certification	June 23, 2022
Company	Skyworth Group
Product Name	Wireless AX3000 Mesh Router
Product Model Variant	RN685
Model Number	RN685
Category	Routers
Sub-category	Access Point for Home or Small Office (Wireless Router)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Alternative topologies	Wi-Fi EasyMesh™
Network management	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2020-12
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED® Certificate

Certification ID: WFA119624

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

V1.0.5beta

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6®

Wi-Fi CERTIFIED 6® (continued)

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
Operating mode subfield in A-Control field
Operating mode indication
Operating mode UL MU Rx
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel
Short Guard Interval
STBC
A-MPDU Tx

Wi-Fi EasyMesh™

Backhaul Link
　　Backhaul in 2.4 GHz
　　Backhaul in 5 GHz low band
　　Backhaul in 5 GHz high band
　　Backhaul over Ethernet
Fronthaul Access Point
　　Fronthaul in 2.4 GHz
　　Fronthaul in 5 GHz low band
　　Fronthaul in 5 GHz high band
Client Capability Query
Agent-initiated Steering capability
Unassociated STA Link Metrics Reporting
Channel Scan on Request

Wi-Fi EasyMesh™ (continued)

Backhaul onboarding with Wi-Fi Protected Setup pushbutton
Coordinated CAC
Traffic separation