



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA121066

Product Info

Date of Certification October 19, 2022

Company Arcadyan Technology Corporation

Product Name Internet-Box 3

Product Model Variant GRV951AZWAX34 1-A-LSW

Model Number GRV951AZWAX34 1-A-LSW

Category Routers

Sub-category Access Point for Home or Small Office (Wireless Router)

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2021-01

Optimization WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-12

WPA™-Enterprise WPA™-Personal





Certification ID: WFA121066

Summary	of	Certificat	tions (cont	inued)
o aiiiiiiai y		O OI CIIIO		COLLE	

Page 2 of 4

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory

Spectrum & Regulatory

Features






Certification ID: WFA121066

Role: Access Point	Page 3 of 4			
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Linux, version: 4.1.52	Bands Supported Transmit (Tx) Receive (Rx			
Wi-Fi Component Firmware	2.4 GHz 3 3			
5.02L07P2_21.2P1				
Wi-Fi Component Operating System	RF Architecture			
Linux, version: 4.1.52	Bands Supported Transmit (Tx) Receive (Rx			
Wi-Fi Component Firmware	5 GHz 4 4			
5.02L07P2_21.2P1				
Certifications				
2.4 GHz Spectrum Capabilities	WPA2™-Enterprise 2018-04			
20 MHz Channel Width in 2.4 GHz	EAP methods			
40 MHz Channel Width in 2.4 GHz				
5 CUz Succéssion Canabilities	WPA2™-Personal 2021-01			
5 GHz Spectrum Capabilities	WPA3™-Enterprise 2020-02 EAP methods			
20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz				
80 MHz Channel Width in 5 GHz	LAI memous			
160 MHz Channel Width in 5 GHz	WPA3™-Personal 2020-12			
Protected Management Frames	WPA™-Enterprise			
Spectrum & Regulatory	WPA™-Personal			
802.11h	Wi-Fi Agile Multiband™			
	Wi-Fi CERTIFIED 6®			







Role: Access Point Page 4 of 4

Wi-Fi CERTIFIED 6® (continued)

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

Operating Mode indication

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx

Wi-Fi Enhanced Open™ 2021-01

Wi-Fi Protected Setup™

PIN

Pushbutton