

Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA121201

Product Info

Date of Certification August 17, 2022

Company Cisco Systems

Product Name Cisco Catalyst 9800-80 Wireless Controller and Cisco CW9162I AP

Product Model Variant Cisco IOS XE: 17.9

Model Number C9800-80 and CW91621

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2021-01

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-12

WPA™-Enterprise WPA™-Personal



Wi-Fi CERTIFIED™ Certificate



Certification ID: WFA121201

Summary	of	Certificat	tions (cont	inued)
Julilliai y	UI	oei iiiica	เเบเเอ	COIIL	IIIucu,

Page 2 of 4

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory

Spectrum & Regulatory

Features



802.11h

Wi-Fi CERTIFIED™ Certificate





Role: Access Point	P	Page 3 of 4				
Vi-Fi Components Vi-Fi Component Operating System	RF Architecture					
Linux, Version: 17.9 Wi-Fi Component Firmware 17.9	Bands Supported 2.4 GHz 5 GHz 6 GHz	Transmit (Tx) 2 2 2	Receive (Rx) 2 2 2			
Certifications						
2.4 GHz Spectrum Capabilities	WMM®	WMM®				
20 MHz Channel Width in 2.4 GHz	WMM®-Power Save					
5 GHz Spectrum Capabilities	Legacy Power Save Unschedule auto PS					
20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	WPA2™-Enterpri	WPA2™-Enterprise 2018-04 EAP methods				
6 GHz Spectrum Capabilities 20 MHz Channel Width in 6 GHz 40 MHz Channel Width in 6 GHz 80 MHz Channel Width in 6 GHz		WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02				
160 MHz Channel Width in 6 GHz Protected Management Frames	EAP methods 192-bit security					
Spectrum & Regulatory	WPA3™-Persona	I 2020-12				
802.11d	WPA™-Enterpris	e				

WPA™-Personal



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA121201



Role: Access Point Page 4 of 4

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Fast Transition OTA on WPA2-Enterprise

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Co-located BSS

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating Mode indication

SU beamformer

SU-MIMO

UL OFDMA

Wi-Fi 6E

Wi-Fi 6 Release 2 features

UL MU Control

UL Extended Range

Target Wake Time information frames

Extended sleep

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx

Wi-Fi Enhanced Open™ 2021-01