



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA121802

Product Info

Date of Certification September 30, 2022

Company Nokia Shanghai Bell Co., Ltd.

Product Name Nokia ONT Beacon G6.2

Product Model Variant Beacon G6.2

Model Number Beacon G6.2

Category Routers

Sub-category Cable, DSL or Other Broadband Gateway (Integrated Home Access

Device)

Summary of Certifications

CLASSIFICATION C	CERTIFICATION
------------------	---------------

Access Wi-Fi Protected Setup™

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-12

WPA™-Enterprise WPA™-Personal





Certification ID: WFA121802

Role: Access Point	Page 2 of 4
1101017100000 1 01111	i ago = oi i

Wi-Fi Components

Wi-Fi Component Operating System

Linux 4.14.180

Wi-Fi Component Firmware

3FE49544

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

WPA3™-Enterprise 2020-02 (continued)

EAP methods

WPA3™-Personal 2020-12

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Wi-Fi CERTIFIED 6®

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time





Certification ID: WFA121802

Role: Access Point Page 3 of 4

Wi-Fi CERTIFIED 6® (continued)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating Mode indication

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel

Wi-Fi CERTIFIED™ n (continued)

Short Guard Interval

STBC

A-MPDU Tx

Wi-Fi Protected Setup™

PIN

Pushbutton





Certification ID: WFA121802

Role: Controller

Wi-Fi Components

Wi-Fi Component Operating System

Linux 4.14.180

Certifications

Wi-Fi EasyMesh™