Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA119895

Product Info

Date of Certification	November 17, 2022
Company	Buffalo Inc.
Product Name	BUFFALO AirStation WNR-3000AX4
Product Model Variant	WNR-3000AX4 Series SKU
Model Number	WNR-3000AX4
Category	Routers
Sub-category	Access Point for Home or Small Office (Wireless Router)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2020-12

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA119895

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

Ver.1.00

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

Ver.1.00

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

Wi-Fi Agile Multiband™ (continued)

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
Operating mode subfield in A-Control field

Wi-Fi CERTIFIED 6® (continued)

Operating mode indication
Operating mode UL MU Rx
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

HT Duplicate Mode
OBSS on Extension Channel
Short Guard Interval
STBC
A-MPDU Tx

Wi-Fi EasyMesh™

Wi-Fi EasyMesh™ (continued)

Backhaul Link
    Backhaul in 2.4 GHz
    Backhaul in 5 GHz low band
    Backhaul over Ethernet
Fronthaul Access Point
    Fronthaul in 2.4 GHz
    Fronthaul in 5 GHz low band
Client Capability Query
Unassociated STA Link Metrics Reporting
Channel Scan on Request
Backhaul onboarding with Wi-Fi Protected Setup pushbutton
Coordinated CAC
Traffic separation

Wi-Fi Protected Setup™

PIN
Pushbutton

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™