



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

### **Certification ID: WFA123966**

#### **Product Info**

**Date of Certification** November 29, 2022

**Company** Mercury Corporation

Product Name G-Box

**Product Model Variant** 2022-11-29

Model Number KG4100

**Category** Routers

**Sub-category** Access Point for Home or Small Office (Wireless Router)

### **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Alternative topologies Wi-Fi EasyMesh™

Network management WMM®

Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Personal 2018-04 WPA3<sup>™</sup>-Personal 2019-08

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



**Certification ID: WFA123966** 



## Role: Access Point Page 2 of 4

#### Wi-Fi Components

Wi-Fi Component Operating System

Linux, version:4.4.198

Wi-Fi Component Firmware

7.1.0.2

#### **RF Architecture**

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

#### Certifications

#### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

#### **5 GHz Spectrum Capabilities**

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

#### **Protected Management Frames**

**WMM®** 

WPA2™-Personal 2018-04

WPA3™-Personal 2019-08

Wi-Fi Agile Multiband™

#### Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

#### Wi-Fi CERTIFIED 6® (continued)

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

**UL OFDMA** 

Wi-Fi CERTIFIED™ a



**Certification ID: WFA123966** 



## Role: Access Point Page 3 of 4

#### Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

#### Wi-Fi CERTIFIED™ b

#### Wi-Fi CERTIFIED™ g

#### Wi-Fi CERTIFIED™ n

HT Duplicate Mode

**OBSS** on Extension Channel

Short Guard Interval

**STBC** 

A-MPDU Tx

#### Wi-Fi EasyMesh™

Backhaul Link

Backhaul in 2.4 GHz

Backhaul in 5 GHz low band

Backhaul in 5 GHz high band

Backhaul over Ethernet

Fronthaul Access Point

Fronthaul in 2.4 GHz

Fronthaul in 5 GHz low band

Fronthaul in 5 GHz high band

Client Capability Query

Unassociated STA Link Metrics Reporting

### Wi-Fi EasyMesh™ (continued)

Backhaul onboarding with Wi-Fi Protected Setup pushbutton

#### Wi-Fi Protected Setup™

PIN

Pushbutton



**Certification ID: WFA123966** 



Role: Controller

Wi-Fi Components

Wi-Fi Component Operating System

Linux, version:4.4.198

Certifications

Wi-Fi EasyMesh™