



# Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: [www.wi-fi.org/certification/programs](http://www.wi-fi.org/certification/programs)



**Certification ID: WFA123966**

## Product Info

Date of Certification	November 29, 2022
Company	Mercury Corporation
Product Name	G-Box
Product Model Variant	2022-11-29
Model Number	KG4100
Category	Routers
Sub-category	Access Point for Home or Small Office (Wireless Router)

## Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™
Security	Protected Management Frames WPA2™-Personal 2018-04 WPA3™-Personal 2019-08 WPA™-Personal



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA123966



Role: Access Point

Page 2 of 4

## Wi-Fi Components

### Wi-Fi Component Operating System

Linux, version:4.4.198

### Wi-Fi Component Firmware

7.1.0.2

### RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

## Certifications

### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz  
40 MHz Channel Width in 2.4 GHz

### 5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz  
40 MHz Channel Width in 5 GHz  
80 MHz Channel Width in 5 GHz

### Protected Management Frames

### WMM®

### WPA2™-Personal 2018-04

### WPA3™-Personal 2019-08

### WPA™-Personal

### Wi-Fi Agile Multiband™

### Wi-Fi CERTIFIED 6®

### Wi-Fi CERTIFIED 6® (continued)

A-MPDU with A-MSDU  
Basic Trigger frame in HE MU PPDU  
BSRP Trigger frame  
Compressed Block Ack Rx (buffer size 256)  
Compressed Block Ack Tx (buffer size 256)  
DL MU-MIMO  
DL OFDMA  
Individual Target Wake Time  
LDPC Rx  
LDPC Tx  
MCS 8-9 Rx  
MCS 8-9 Tx  
MCS 10-11 Rx  
MCS 10-11 Tx  
MU EDCA Parameter Set element  
MU-BAR Trigger frame  
MU-RTS Trigger frame  
M-BSSID  
Operating Mode indication  
SU beamformer  
TXOP RTS Threshold  
UL OFDMA

### Wi-Fi CERTIFIED™ a



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA123966



Role: Access Point

Page 3 of 4

## Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support  
A-MPDU with A-MSDU  
DL MU-MIMO  
LDPC Rx  
LDPC Tx  
MCS 8-9 Rx  
Short Guard Interval  
STBC  
SU beamformer

## Wi-Fi EasyMesh™ (continued)

Backhaul onboarding with Pushbutton

## Wi-Fi Protected Setup™

PIN  
Pushbutton

## Wi-Fi CERTIFIED™ b

## Wi-Fi CERTIFIED™ g

## Wi-Fi CERTIFIED™ n

HT Duplicate Mode  
OBSS on Extension Channel  
Short Guard Interval  
STBC  
A-MPDU Tx

## Wi-Fi EasyMesh™

Backhaul Link  
    Backhaul in 2.4 GHz  
    Backhaul in 5 GHz low band  
    Backhaul in 5 GHz high band  
    Backhaul over Ethernet  
Fronthaul Access Point  
    Fronthaul in 2.4 GHz  
    Fronthaul in 5 GHz low band  
    Fronthaul in 5 GHz high band  
Client Capability Query  
Unassociated STA Link Metrics Reporting



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA123966



Role: Controller

Page 4 of 4

## Wi-Fi Components

### Wi-Fi Component Operating System

Linux, version:4.4.198

## Certifications

Wi-Fi EasyMesh™