Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA124034

Product Info

Date of Certification	June 8, 2023
Company	Grandstream Networks, Inc.
Product Name	In-Wall Wi-Fi 6 Access Point
Product Model Variant	GWN7661
Model Number	GWN7661
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Passpoint® Release 3
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2022-06 WPA™-Enterprise WPA™-Personal

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA124034

Wi-Fi Components

Wi-Fi Component Operating System

linux 4.4.60

Wi-Fi Component Firmware

0.4.11.4(init)

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Passpoint® Release 3

Online Sign Up and Policy provisioning
Online Sign Up using single SSID
Roaming Consortium Selection
Venue Information
Terms and Conditions

Protected Management Frames

WMM®

WPA2™-Enterprise 2018-04

WPA2™-Enterprise 2018-04 (continued)

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
192-bit security

WPA3™-Personal 2022-06

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Cellular Data aware

Wi-Fi CERTIFIED 6®

Wi-Fi CERTIFIED 6® (continued)

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode indication

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

Wi-Fi CERTIFIED™ ac (continued)

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC