Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA124037

Product Info

Date of Certification	June 9, 2023
Company	Grandstream Networks, Inc.
Product Name	Indoor Wi-Fi 6 Access Point
Product Model Variant	GWN7662
Model Number	GWN7662
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Passpoint® Release 3
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2022-06 WPA™-Enterprise WPA™-Personal

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA124037

Wi-Fi Components

Wi-Fi Component Operating System

linux 5.4.164

Wi-Fi Component Firmware

0.4.11.4(init)

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Passpoint® Release 3

Roaming Consortium Selection
Venue Information
Terms and Conditions

Protected Management Frames

WMM®

WPA2™-Enterprise 2018-04

WPA2™-Enterprise 2018-04 (continued)

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
192-bit security

WPA3™-Personal 2022-06

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Cellular Data aware

Wi-Fi CERTIFIED 6®

Wi-Fi CERTIFIED 6® (continued)

4 antenna support
A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode indication
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval

Wi-Fi CERTIFIED™ ac (continued)

STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval
STBC