



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA119739

Product Info

Date of Certification December 29, 2022

Company CROSSCALL

Product Name Core-Z5

Product Model Variant Add Wi-Fi 6E for STA

Model Number Core-Z5

Category Phones

Sub-category Smartphone

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 3

Wi-Fi Easy Connect™ Wi-Fi Protected Setup™

Applications & Services Voice-Enterprise

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2021-01

Optimization TDLS

WMM®

WMM®-Admission Control WMM®-Power Save

Wi-Fi Agile Multiband™

Wi-Fi Optimized Connectivity™ 2020





Certification ID: WFA119739

| Summary of Certifications (continued) | | Page 2 of 7 |
|---------------------------------------|---|-------------|
| CLASSIFICATION | CERTIFICATION | |
| Security | Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-12 WPA™-Enterprise WPA™-Personal | |





Certification ID: WFA119739

| Role: Access Point | Page 3 of 7 |
|--------------------|-------------|
| | |

Wi-Fi Components

Wi-Fi Component Operating System

Android 12

Wi-Fi Component Firmware

WLAN.MSL.1.0.1-00848-QCAMSLSWPLZ-1.499409.2

RF Architecture

| Bands Supported | Transmit (Tx) | Receive (Rx) |
|-----------------|---------------|--------------|
| 2.4 GHz | 2 | 2 |
| 5 GHz | 2 | 2 |

Certifications

20 MHz Channel Width in 2.4 GHz

A-MPDU with A-MSDU LDPC Rx

LDPC Tx

5 GHz Spectrum Capabilities

Protected Management Frames

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

LDPC Rx

LDPC Tx

Short Guard Interval

WMM®-Power Save

Unschedule auto PS

WMM®

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

WPA2™-Personal 2021-01

WPA3™-Personal 2020-12

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel

Short Guard Interval

A-MPDU Tx

Wi-Fi CERTIFIED 6®







Role: Station Page 4 of 7

Wi-Fi Components

Wi-Fi Component Operating System

Android 12

Wi-Fi Component Firmware

WLAN.MSL.1.0.1-00848-QCAMSLSWPLZ-1.499409.2

RF Architecture

| Bands Supported | Transmit (Tx) | Receive (Rx) |
|-----------------|---------------|--------------|
| 2.4 GHz | 2 | 2 |
| 5 GHz | 2 | 2 |
| 6 GHz | 2 | 2 |

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

Passpoint® Release 3 (continued)

Network Information in network selection

Online Sign Up and Policy provisioning

ANQP-element for OSU provider selection

Online Sign Up using single SSID

Venue Information

Terms and Conditions

Roaming Consortium Selection

6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz

40 MHz Channel Width in 6 GHz

80 MHz Channel Width in 6 GHz

Protected Management Frames

TDLS

Voice-Enterprise

WMM®

Passpoint® Release 3

Display and input method

Display of HS2.0 indication

SIM credentials

USIM Credentials

Network Icon support

WMM®-Admission Control

WMM®-Power Save

Legacy Power Save

Unschedule auto PS





Certification ID: WFA119739

Role: Station Page 5 of 7

WPA2[™]-Enterprise 2018-04

EAP methods

EAP AKA

EAP AKA Prime

EAP SIM

EAP TLS

EAP TTLS

PEAPv0

PEAPv1

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods

EAP AKA

EAP AKA Prime

EAP SIM

EAP TLS

EAP TTLS

PEAPv0

PEAPv1

192-bit security

Server Certificate Validation

WPA3™-Personal 2020-12

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

ANQP

Beacon Report Measurement Active Mode

Wi-Fi Agile Multiband™ (continued)

Beacon Report Measurement Passive Mode

BTM Query

Cellular Data capable

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

DL Mu PPDU multi-tone

DL MU-MIMO

HE NDP

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

OM Control field Tx

OM subfield in A-Control field

Operating Mode indication

SU beamformee

SU-MIMO

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi 6E

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac





Certification ID: WFA119739

Role: Station Page 6 of 7 Wi-Fi CERTIFIED™ ac (continued) Wi-Fi Protected Setup™ (continued) A-MPDU with A-MSDU PIN DL MU-MIMO Pushbutton LDPC Rx MCS 8-9 Rx Short Guard Interval STBC LDPC Tx SU beamformee Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n STBC A-MPDU Tx **OBSS** on Extension Channel **Power Management** Short Guard Interval Wi-Fi Easy Connect™ Bootstrapping methods QR code responder Public Key Exchange (PKEX) Wi-Fi Enhanced Open™ 2021-01 Wi-Fi Optimized Connectivity™ 2020 Pushbutton Wi-Fi Protected Setup™





Certification ID: WFA119739

| Role: Configurator | Page 7 of 7 | | |
|--|-----------------|---------------|--------------|
| Wi-Fi Components | | | |
| Wi-Fi Component Operating System | RF Architecture | | |
| Android 12 | Bands Supported | Transmit (Tx) | Receive (Rx) |
| Wi-Fi Component Firmware WLAN.MSL.1.0.1-00848-QCAMSLSWPLZ- | 2.4 GHz | 2 | 2 |
| 1.499409.2 | 5 GHz | 2 | 2 |
| Certifications Wi-Fi Easy Connect™ | | | |
| Provisioning Configurator | | | |
| | | | |