



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA114027

Product Info

Date of Certification March 6, 2023

Company Huawei Device Co., Ltd.

Product Name Smart Phone

Product Model Variant NAM-LX9 2023-3-6 update 11n

Model Number NAM-LX9

Category Phones

Sub-category Smartphone

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ ac
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Direct®

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-02





Certification ID: WFA114027

Summary	of Certifica	ations	cont	inued)
Gaillia				III a c a ,

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory

Spectrum & Regulatory

Features



Certification ID: WFA114027



Role: Access Point Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

EMUI 13.0Based on Android

Wi-Fi Component Firmware

HL1NTHM

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities Wi-Fi CERTIFIED™ ac (continued)

20 MHz Channel Width in 2.4 GHz STBC

Wi-Fi CERTIFIED™ b

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2020-02

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC



Certification ID: WFA114027



Role: Station Page 4 of 5

Wi-Fi Components

Wi-Fi Component Operating System

EMUI 13.0Based on Android

Wi-Fi Component Firmware

HL1NTHM

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

WPA2™-Enterprise 2018-04

EAP methods

EAP AKA

EAP AKA Prime

EAP SIM

EAP TLS

EAP TTLS

PEAPv0

PEAPv1

WPA2™-Personal 2021-01

Protected Management Frames

Spectrum & Regulatory

802.11h

WMM®

WMM®-Power Save

Legacy Power Save Unschedule auto PS

WPA3™-Enterprise 2020-02

EAP methods

EAP AKA

EAP AKA Prime

EAP SIM

EAP TLS

EAP TTLS

PEAPv0

PEAPv1

Server Certificate Validation

WPA3™-Personal 2020-02





Certification ID: WFA114027

Role: Station Page 5 of 5

Wi-Fi Agile Multiband™

Beacon Report Measurement Active Mode

Wi-Fi CERTIFIED™ ac (continued)

SU beamformee

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

DL MU PPDU multi-tone

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode indication

SU beamformee

SU-MIMO

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC

Wi-Fi Direct®

Wi-Fi Protected Setup™

Pushbutton

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

STBC

LDPC Tx