



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

#### **Certification ID: WFA126059**

#### **Product Info**

**Date of Certification** February 20, 2024

Company MediaTek Inc.

Product Name MediaTek Filogic 380 - MT7927

Product Model Variant NA

Model Number MediaTek Filogic 380 - MT7927

**Category** Other

**Sub-category** Reference Design

#### **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Direct®

Wi-Fi Enhanced Open™ 2021-01

**Optimization** WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2022-12 WPA3<sup>™</sup>-Personal 2022-06





**Certification ID: WFA126059** 

Summary of Certifications (continued)		Page 2 of 5
CLASSIFICATION	CERTIFICATION	
Security	WPA™-Enterprise WPA™-Personal	
Spectrum & Regulatory Features	Spectrum & Regulatory	



Certification ID: WFA126059



Role: Station		Pa	age 3 of 5	
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Windows	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware	2.4 GHz	2	2	
Windows11	5 GHz	2	2	
	6 GHz	2	2	
Certifications				
2.4 GHz Spectrum Capabilities	Spectrum & Regu	Spectrum & Regulatory (continued)		
20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz	802.11h			
5 GHz Spectrum Capabilities	WMM®			
20 MHz Channel Width in 5 GHz	WMM®-Power Sa	ve		
40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	Unschedule auto PS			
160 MHz Channel Width in 5 GHz	WPA2™-Enterpris	se 2018-04		
6 GHz Spectrum Capabilities	EAP methods			
20 MHz Channel Width in 6 GHz	EAP TLS PEAPv0			
40 MHz Channel Width in 6 GHz 80 MHz Channel Width in 6 GHz				
160 MHz Channel Width in 6 GHz	WPA2™-Persona	2021-01		
Protected Management France	WPA3™-Enterpris	se 2022-12		
Protected Management Frames	EAP methods			
Spectrum & Regulatory	EAP TLS PEAPv0			





**Certification ID: WFA126059** 

Role: Station Page 4 of 5

WPA3<sup>™</sup>-Enterprise 2022-12 (continued)

192-bit security

Server Certificate Validation

WPA3™-Personal 2022-06

WPA™-Enterprise

**WPA™-Personal** 

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL Mu PPDU multi-tone

LDPC Tx

LDPC Rx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

OM subfield in A-Control field

Operating Mode indication

SU beamformee

SU-MIMO

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi 6E

Wi-Fi CERTIFIED 6® (continued)

Multiple M-BSSID

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode

**OBSS** on Extension Channel

Short Guard Interval

Wi-Fi Direct®

Wi-Fi Enhanced Open™ 2021-01

Wi-Fi Protected Setup™

PIN





**Certification ID: WFA126059** 

Role: Station	Page 5 of 5
Wi-Fi Protected Setup™ (continued)	
Pushbutton	