



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA101303

Product Info

Date of Certification June 5, 2023

Company HiSilicon Technologies Co., Ltd.

Product Name Hi1105C20

Product Model Variant Hi1105 0605update

Model Number Hi1105V100C20

Category Phones

Sub-category Smartphone

Summary of Certifications

CLASSIFICATION CERTIFICATION

Applications & Services Voice-Enterprise

Wi-Fi Location™ R1

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Direct®

Optimization WMM®

WMM®-Admission Control

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2018-04 WPA3[™]-Enterprise 2018-04 WPA3[™]-Personal 2019-08





Certification ID: WFA101303

Summary of Certificat	tions (continued)	Page 2 of 7
CLASSIFICATION	CERTIFICATION	
Security	WPA™-Enterprise WPA™-Personal	
Spectrum & Regulatory Features	Spectrum & Regulatory	



Certification ID: WFA101303



Role: Access Point Page 3 of 7

Wi-Fi Components

Wi-Fi Component Operating System

HarmonyOS

Wi-Fi Component Firmware

Hi1105V100C20

RF Architecture

MCS 8-9 Rx

MCS 8-9 Tx MCS 10-11 Rx MCS 10-11 Tx

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

Wi-Fi CERTIFIED 6® (continued)

5 GHz

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Personal 2018-04

WPA3™-Personal 2019-08

Wi-Fi CERTIFIED 6®

Compressed Block Ack Rx (buffer size 256)

LDPC Rx

LDPC Tx

Wi-Fi CERTIFIED™ ac Extended 5 GHz Channel Support

RTS with BW Signaling

Operating Mode indication

Wi-Fi CERTIFIED™ a

A-MPDU with A-MSDU

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n





Certification ID: WFA101303

Role: Access Point Wi-Fi CERTIFIED™ n (continued) A-MPDU Tx HT Duplicate Mode OBSS on Extension Channel Short Guard Interval STBC



WMM®-Power Save

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA101303



Role: Station			Page 5 of 7	
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
HarmonyOS	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware	2.4 GHz	2	2	
Hi1105V100C20	5 GHz	2	2	
Certifications				
2.4 GHz Spectrum Capabilities	WMM®-Power Sav	ve (continued)		
20 MHz Channel Width in 2.4 GHz	Legacy Power Save			
40 MHz Channel Width in 2.4 GHz	Unschedule auto PS			
5 GHz Spectrum Capabilities	WPA2™-Enterpris	se 2018-04		
20 MHz Channel Width in 5 GHz	EAP methods			
40 MHz Channel Width in 5 GHz	EAP AKA			
80 MHz Channel Width in 5 GHz	EAP AKA Prime			
160 MHz Channel Width in 5 GHz	EAP SIM EAP TLS			
	EAP TTLS			
Protected Management Frames	PEAPv0			
Spectrum & Regulatory	PEAPv1			
802.11h	WPA2™-Personal	2018-04		
Voice-Enterprise	WPA3™-Enterpris	se 2018-04		
WMM®	EAP methods EAP AKA			
	EAP AKA EAP AKA Prime			
WMM®-Admission Control	EAP SIM			
	EAP TLS			





Certification ID: WFA101303

Role: Station Page 6 of 7

WPA3™-Enterprise 2018-04 (continued)

EAP TTLS

PEAPv0

PEAPv1

WPA3™-Personal 2019-08

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Cellular Data capable

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

DL Mu PPDU multi-tone

DL MU-MIMO

HE NDP

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

OM Control field Tx

Wi-Fi CERTIFIED 6® (continued)

OM subfield in A-Control field

Operating Mode indication

SU beamformee

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

STBC

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode

OBSS on Extension Channel

Power Management

Short Guard Interval

STBC





Certification ID: WFA101303

Role: Station	Page 7 c
Wi-Fi Direct®	
Wi-Fi Location™ R1	
Fine Timing Measurement 2017	