Wi-Fi CERTIFIED® Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA126699

Product Info

Date of Certification	June 6, 2023
Company	Huawei Technologies Co., Ltd.
Product Name	GPON Terminal
Product Model Variant	Huawei OptiXstar HG8245X6-8N-30
Model Number	Huawei OptiXstar HG8245X6-8N-30
Category	Routers
Sub-category	Access Point for Home or Small Office (Wireless Router)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Alternative topologies	Wi-Fi EasyMesh™
Network management	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-02
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Spectrum & Regulatory Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED® Certificate

Certification ID: WFA126699

Wi-Fi Components

Wi-Fi Component Operating System
Linux

Wi-Fi Component Firmware
V5

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d
802.11h

WMM®

WMM®-Power Save

Legacy Power Save

WMM®-Power Save (continued)

Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods

WPA3™-Personal 2020-02

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED 6®

4 antenna support
A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
Beamforming sounding

Wi-Fi CERTIFIED 6® (continued)

BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode subfield in A-Control field
Operating mode indication
Operating mode UL MU Rx
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling
Extended 5 GHz Channel Support
A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC

Wi-Fi CERTIFIED™ ac (continued)

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval
STBC

Wi-Fi Protected Setup™

PIN
Pushbutton

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Operating System

RTOS

Certifications

Wi-Fi EasyMesh™