Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA126716

Product Info	
Date of Certification	September 19, 2023
Company	Chongqing SeekWave Technology Co. Ltd
Product Name	EA6652
Product Model Variant	EA6652
Model Number	EA6652
Category	Other
Sub-category	Chipset

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Network management	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2022-06 Wi-Fi Enhanced Open™ 2021-01
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Spectrum & Regulatory Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi Components

Wi-Fi Component Operating System
RTOS

Wi-Fi Component Firmware
V1.0

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d
802.11h

WMM®

WPA2™-Enterprise 2018-04

EAP methods
    EAP TLS

WPA2™-Enterprise 2018-04 (continued)

    EAP TTLS
    PEAPv0
    PEAPv1

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
    EAP TLS
    EAP TTLS
    PEAPv0
    PEAPv1
Server Certificate Validation

WPA3™-Personal 2022-06

Wi-Fi Agile Multiband™

ANQP
ANQP-based Neighbor report
Beacon Report Measurement Active Mode
Beacon Report Measurement Passive Mode

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA126716

Wi-Fi Agile Multiband™ (continued)

BTM Query

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

LDPC Tx

LDPC Rx

Individual Target Wake Time

MCS 10-11 Rx

MCS 10-11 Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode control field

Operating mode subfield in A-Control field

Operating mode indication

SU beamformee

SU-MIMO

UL OFDMA

Wi-Fi 6 Release 2 features

  UL MU-MIMO

  UL MU Control

  UL Extended Range

  Target Wake Time information frames

  Broadcast Target Wake Time

  Extended sleep time

Wi-Fi CERTIFIED 6® Release 2 (continued)

  M-BSSID control frames

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

STBC

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

RIFS

Power Management

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2021-01