



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA118214

Product Info

Date of Certification	August 28, 2023
Company	Zebra Technologies
Product Name	TC58
Product Model Variant	2023-06-14
Model Number	TC58
Category	Phones
Sub-category	Phone, multi-mode (Wi-Fi and other)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Passpoint® Release 3
Applications & Services	Voice-Enterprise
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Direct® Wi-Fi Enhanced Open™ 2021-01
Optimization	WMM® WMM®-Admission Control WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi Optimized Connectivity™ 2020 Wi-Fi QoS Management™



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA118214



Summary of Certifications (continued)

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Security

Protected Management Frames

WPA2™-Enterprise 2018-04

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

WPA3™-Personal 2022-06

WPA™-Enterprise

WPA™-Personal

Spectrum & Regulatory Features

Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA118214



Role: Station

Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Android, version:13

Wi-Fi Component Firmware

1.1.2.0.866.5

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2
6 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz

40 MHz Channel Width in 6 GHz

80 MHz Channel Width in 6 GHz

160 MHz Channel Width in 6 GHz

Passpoint® Release 3

Display and input method

Display of HS2.0 indication

NAI Home Realm Query element

Passpoint® Release 3 (continued)

Operating Class Indication

SIM credentials

USIM Credentials

Network Icon support

Network Information in network selection

Online Sign Up and Policy provisioning

Fast Transition OTA on WPA2-Enterprise

ANQP-element for OSU provider selection

Online Sign Up using single SSID

Venue Information

Terms and Conditions

Roaming Consortium Selection

Protected Management Frames

Spectrum & Regulatory

802.11h

Voice-Enterprise

WMM®



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA118214



Role: Station

Page 4 of 5

WMM®-Admission Control

WMM®-Power Save

Legacy Power Save
Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods
EAP AKA
EAP AKA Prime
EAP SIM
EAP TLS
EAP TTLS
PEAPv0
PEAPv1

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
EAP AKA
EAP AKA Prime
EAP SIM
EAP TLS
EAP TTLS
PEAPv0
PEAPv1
192-bit security
192-bit security RSA 3K with the
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
cipher suite
Fast Transition OTA on WPA3-Enterprise
Fast Transition OTA on WPA3-Enterprise transition mode
Fast Transition OTDS on WPA3-Enterprise
Server Certificate Validation

WPA3™-Personal 2022-06

Fast Transition OTA on WPA3-Personal
Fast Transition OTA on WPA3-Personal transition mode
Fast Transition OTDS on WPA3-Personal

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

ANQP
ANQP-based Neighbor report
Beacon Report Measurement Active Mode
Beacon Report Measurement Passive Mode
BTM Query
Fast Transition OTA on WPA2-Personal
Fast Transition OTA on WPA2-Enterprise

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU
Beamforming sounding
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL Mu PPDU multi-tone
HE NDP
LDPC Tx
LDPC Rx
Individual Target Wake Time
MCS 10-11 Rx
MCS 10-11 Tx
MCS 8-9 Rx
MCS 8-9 Tx



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA118214



Role: Station

Page 5 of 5

Wi-Fi CERTIFIED 6® Release 2 (continued)

- MU EDCA Parameter Set element
- MU-BAR Trigger frame
- MU-RTS Trigger frame
- OM Control field Tx
- OM subfield in A-Control field
- Operating Mode indication
- SU beamformee
- SU-MIMO
- UL OFDMA
- UL TB PPDU multi-tone
- Wi-Fi 6E
 - Multiple M-BSSID
- Wi-Fi 6 Release 2 features
 - UL MU-MIMO
 - UL MU Control
 - Target Wake Time information frames
 - Broadcast Target Wake Time
 - M-BSSID control frames

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

- Extended 5 GHz Channel Support
- RTS with BW Signaling
- A-MPDU with A-MSDU
- DL MU-MIMO
- LDPC Rx
- MCS 8-9 Rx
- Short Guard Interval
- STBC
- LDPC Tx
- SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

- A-MPDU Tx
- OBSS on Extension Channel
- Short Guard Interval
- STBC

Wi-Fi Direct®

Wi-Fi Enhanced Open™ 2021-01

Wi-Fi Optimized Connectivity™ 2020

- Active Scan
- Fast Transition OTA on WPA2-Enterprise
- Pushbutton
- Probe Deferral and Suppression

Wi-Fi QoS Management™

- Default DSCP to UP mapping
- DSCP QoS Map
- Mirrored Stream Classification Service
 - MSCS setup at association
- Stream Classification Service