



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA127018

Product Info

Date of Certification June 28, 2023

Company Huawei Technologies Co., Ltd.

Product Name GPON Terminal

Product Model Variant Huawei OptiXstar EG8245X6-8N-30

Model Number Huawei OptiXstar EG8245X6-8N-30

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Alternative topologies Wi-Fi EasyMesh™

Network management WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-02

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Spectrum & Regulatory
Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



Certification ID: WFA127018



Role: Access Point	Page 2 of 4			
Wi-Fi Components Wi-Fi Component Operating System	RF Architecture			
Linux Wi-Fi Component Firmware V5	Bands Supported 2.4 GHz 5 GHz	Transmit (Tx) 4 4	Receive (Rx) 4 4	
Certifications				
2.4 GHz Spectrum Capabilities	WMM®-Power Save (continued) Unschedule auto PS			
20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz				
5 GHz Spectrum Capabilities	WPA2™-Enterpris	e 2018-04		
20 MHz Channel Width in 5 GHz	EAF Illetilous			
40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	WPA2™-Personal 2021-01			
	WPA3™-Enterpris	e 2020-02		
Protected Management Frames	EAP methods			
Spectrum & Regulatory	WPA3™-Personal	2020-02		
802.11d 802.11h	Wi-Fi Agile Multib	and™		
WMM®	Wi-Fi CERTIFIED (6 ®		
WMM®-Power Save	4 antenna support A-MPDU with A-MSDU			
Legacy Power Save	Basic Trigger frame in HE MU PPDU Beamforming sounding			



Certification ID: WFA127018



Role: Access Point Page 3 of 4

Wi-Fi CERTIFIED 6® (continued)

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

Wi-Fi CERTIFIED™ ac (continued)

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC

Wi-Fi Protected Setup™

PIN

Pushbutton



Certification ID: WFA127018



Role: Controller	Page 4 of 4
Wi-Fi Components	
Wi-Fi Component Operating System	
Linux	
Wi-Fi Component Operating System RTOS	
Certifications	
Wi-Fi EasyMesh™	