



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA127198

Product Info

Date of Certification April 19, 2024

Company Faurecia Clarion Electronics Co., Ltd.

Product Name Rear Monitor

Product Model Variant D2301

Model Number D2301

Category Other

Sub-category In-vehicle Network

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Applications & Services Miracast®

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi Direct®

Optimization WMM®

Security Protected Management Frames

WPA2[™]-Personal 2021-01 WPA3[™]-Personal 2022-06



Certification ID: WFA127198



Role: Access Point Page 2 of 4

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

wI0

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

5 GHz 1

Certifications

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Short Guard Interval

A-MPDU Tx

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2022-06

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

Wi-Fi CERTIFIED™ n

HT Duplicate Mode





Certification ID: WFA127198

| Role: Station | | P | age 3 of 4 | |
|--|-----------------------------|---------------------------------|--------------|--|
| Vi-Fi Components | | | | |
| Wi-Fi Component Operating System | RF Architecture | | | |
| Linux | Bands Supported | Transmit (Tx) | Receive (Rx) | |
| Wi-Fi Component Firmware wl0 | 2.4 GHz | 1 | 1 | |
| | 5 GHz | 1 | 1 | |
| Certifications | | | | |
| 2.4 GHz Spectrum Capabilities | Wi-Fi CERTIFIED | Wi-Fi CERTIFIED™ ac (continued) | | |
| 20 MHz Channel Width in 2.4 GHz | STBC LDPC Tx | LDPC Tx | | |
| 5 GHz Spectrum Capabilities | SU beamformee | | | |
| 20 MHz Channel Width in 5 GHz | Wi-Fi CERTIFIED™ b | | | |
| 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz | Wi-Fi CERTIFIED™ g | | | |
| Protected Management Frames | Wi-Fi CERTIFIED | Wi-Fi CERTIFIED™ n | | |
| WMM® | A-MPDU Tx HT Duplicate Mode | | | |
| WPA2™-Personal 2021-01 | OBSS on Extension C | OBSS on Extension Channel | | |
| | Short Guard Interval STBC | | | |
| WPA3™-Personal 2022-06 | | | | |
| Wi-Fi CERTIFIED™ a | Wi-Fi Direct® | | | |
| Wi-Fi CERTIFIED™ ac | Wi-Fi Protected S | Wi-Fi Protected Setup™ | | |
| LDPC Rx | PIN | | | |
| MCS 8-9 Rx Short Guard Interval | Pushbutton | | | |





Certification ID: WFA127198

| Page 4 of 4 | | |
|-----------------|-------------------------|---|
| | | |
| RF Architecture | | |
| Bands Supported | Transmit (Tx) | Receive (Rx) |
| 2.4 GHz | 1 | 1 |
| 5 GHz | 1 | 1 |
| | | |
| | | |
| | Bands Supported 2.4 GHz | RF Architecture Bands Supported Transmit (Tx) 2.4 GHz 1 |