Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA127308

Product Info

Date of Certification	September 21, 2023
Company	Allied Telesis Holdings K.K.
Product Name	AT-TQ7403
Product Model Variant	New Product Model
Model Number	AT-TQ7403
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Passpoint® Release 3
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Enhanced Open™ 2021-01
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2022-06 WPA™-Enterprise

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA127308

CLASSIFICATION	CERTIFICATION
Security	WPA™-Personal
Spectrum & Regulatory Features	Spectrum & Regulatory

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.8-01573-QCAHKSWPL_SILICONZ-2.28823.8 v1

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
6 GHz	2	2

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.8-01573-QCAHKSWPL_SILICONZ-2.28823.8 v1

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.8-01573-QCAHKSWPL_SILICONZ-2.28823.8 v1

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz

6 GHz Spectrum Capabilities (continued)

40 MHz Channel Width in 6 GHz
80 MHz Channel Width in 6 GHz
160 MHz Channel Width in 6 GHz

Passpoint® Release 3

Roaming Consortium Selection
Terms and Conditions
Venue Information

Protected Management Frames

Spectrum & Regulatory

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA127308

Spectrum & Regulatory (continued)

802.11d
802.11h

WMM®

WMM®-Power Save

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
192-bit security
Fast Transition OTA on WPA3-Enterprise
Fast Transition OTA on WPA3-Enterprise transition mode

WPA3™-Personal 2022-06

Fast Transition OTA on WPA3-Personal
Fast Transition OTA on WPA3-Personal transition mode

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Cellular Data aware

Wi-Fi Agile Multiband™ (continued)

Fast Transition OTA on WPA2-Enterprise
Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
Co-located BSS
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode indication
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA
Wi-Fi 6E
　Multiple M-BSSID
Wi-Fi 6 Release 2 features
　UL Extended Range
　Target Wake Time information frames
　Extended sleep

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA127308

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2021-01