Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA112295

Product Info

Date of Certification	July 17, 2023
Company	Huawei Device Co., Ltd.
Product Name	HUAWEI MatePad Pro
Product Model Variant	MRR-W29 update WPA2 enterprise 20230717
Model Number	MRR-W29
Category	Tablets, Ereaders & Cameras
Sub-category	Tablet (Wi-Fi and other)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Direct®
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-02

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA112295

Wi-Fi Components

Wi-Fi Component Operating System

HarmonyOS

Wi-Fi Component Firmware

WLAN.HST.1.0.1.R1

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WMM®-Power Save

Legacy Power Save
Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods
    EAP TLS
    EAP TTLS

WPA2™-Enterprise 2018-04 (continued)

    PEAPv0
    PEAPv1

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods
    EAP TLS
    EAP TTLS
    PEAPv0
    PEAPv1
Server Certificate Validation

WPA3™-Personal 2020-02

Wi-Fi Agile Multiband™

ANQP
ANQP-based Neighbor report
Cellular Data capable
Fast Transition OTA on WPA2-Personal
Fast Transition OTA on WPA2-Enterprise

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA112295

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode control field

Operating mode subfield in A-Control field

Operating mode indication

SU beamformee

SU-MIMO

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

Wi-Fi CERTIFIED™ ac (continued)

STBC

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Power Management

Short Guard Interval

STBC

Wi-Fi Direct®

Wi-Fi Protected Setup™

Pushbutton