



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA126058

Product Info

| | |
|------------------------------|---|
| Date of Certification | November 16, 2023 |
| Company | Hitron Technologies |
| Product Name | CODA5519W |
| Product Model Variant | CODA5519W-WPS2.0 |
| Model Number | CODA5519W |
| Category | Routers |
| Sub-category | Cable, DSL or Other Broadband Gateway (Integrated Home Access Device) |

Summary of Certifications

| CLASSIFICATION | CERTIFICATION |
|---|---|
| Access | Wi-Fi Protected Setup™ |
| Connectivity | 2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n |
| Optimization | WMM® Wi-Fi Agile Multiband™ |
| Security | Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2022-06 |
| Spectrum & Regulatory Features | Spectrum & Regulatory |



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA126058



Role: Access Point

Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Linux Kernel 5.15.77

Wi-Fi Component Firmware

WLAN6.2.0.114

RF Architecture

| Bands Supported | Transmit (Tx) | Receive (Rx) |
|-----------------|---------------|--------------|
| 2.4 GHz | 4 | 4 |
| 5 GHz | 4 | 4 |

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2022-06

Wi-Fi Agile Multiband™

Wi-Fi Agile Multiband™ (continued)

Cellular Data aware

Wi-Fi CERTIFIED 6® Release 2

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating Mode indication



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA126058



Role: Access Point

Page 3 of 3

Wi-Fi CERTIFIED 6® Release 2 (continued)

SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA
Wi-Fi 6 Release 2 features
 UL MU-MIMO
 UL MU Control
 UL Extended Range
 M-BSSID control frames

Wi-Fi CERTIFIED™ n (continued)

Short Guard Interval
STBC

Wi-Fi Protected Setup™

PIN
Pushbutton

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling
Extended 5 GHz Channel Support
A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel