Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA121231

Product Info

Date of Certification	December 15, 2023
Company	Alcatel-Lucent Enterprise dba ALE USA Inc.
Product Name	OmniAccess Stellar
Product Model Variant	Add 160M
Model Number	OAW-AP1451
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Passpoint® Release 3
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-12 WPA™-Enterprise WPA™-Personal

This certificate was downloaded on **2024-05-19** at **23:15:37** UTC

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA121231

Wi-Fi Components

Wi-Fi Component Operating System

Linux4.4

Wi-Fi Component Firmware

SPF.11.4

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	8	8
6 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz
40 MHz Channel Width in 6 GHz
80 MHz Channel Width in 6 GHz
160 MHz Channel Width in 6 GHz

Passpoint® Release 3

Online Sign Up and Policy provisioning
Online Sign Up using single SSID
Roaming Consortium Selection

Passpoint® Release 3 (continued)

Venue Information
Terms and Conditions

Protected Management Frames

WMM®

WMM®-Power Save

Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods

WPA3™-Personal 2020-12

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Cellular Data aware

Wi-Fi CERTIFIED 6®

4 antenna support
A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
Beamforming sounding
BSRP Trigger frame
Co-located BSS
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode indication
SU beamformer
SU-MIMO

Wi-Fi CERTIFIED 6® (continued)

TXOP RTS Threshold
UL OFDMA
Wi-Fi 6E
    Multiple M-BSSID

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8 Rx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel
Short Guard Interval
STBC
A-MPDU Tx