



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA127760

Product Info

| | |
|-----------------------|---|
| Date of Certification | January 5, 2024 |
| Company | Broadcom Corporation |
| Product Name | BCM94916R6726W7 |
| Product Model Variant | Wi-Fi 7 |
| Model Number | BCM94916R6726W7 |
| Category | Routers |
| Sub-category | Access Point for Home or Small Office (Wireless Router) |

Summary of Certifications

| CLASSIFICATION | CERTIFICATION |
|----------------|--|
| Connectivity | 2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED 7™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n |
| Optimization | WMM® Wi-Fi Agile Multiband™ |
| Security | Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2023-12 WPA™-Enterprise WPA™-Personal |



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA127760



Summary of Certifications (continued)

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory
Features

Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA127760



Role: Access Point

Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

17.10.373.9

RF Architecture

| Bands Supported | Transmit (Tx) | Receive (Rx) |
|-----------------|---------------|--------------|
| 2.4 GHz | 4 | 4 |
| 5 GHz | 4 | 4 |
| 6 GHz | 4 | 4 |

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

Spectrum & Regulatory (continued)

802.11d
802.11h

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

WMM®

Max Throughput

WPA2™-Enterprise 2018-04

EAP methods

6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz
40 MHz Channel Width in 6 GHz
80 MHz Channel Width in 6 GHz
160 MHz Channel Width in 6 GHz
320 MHz channel width in 6 GHz

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
192-bit security

Protected Management Frames

WPA3™-Personal 2023-12

Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA127760



Role: Access Point

Page 4 of 5

WPA3™-Personal 2023-12 (continued)

AKM 24
Beacon Protection
SAE-Public Key

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

4 antenna support
A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
Beamforming sounding
BSRP Trigger frame
Co-located BSS
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame

Wi-Fi CERTIFIED 6® Release 2 (continued)

Operating Mode indication
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA
Wi-Fi 6E
Wi-Fi 6 Release 2 features
UL MU-MIMO
UL MU Control
UL Extended Range
Target Wake Time information frames
Extended sleep
Dynamic MU SMPS
Preamble Puncturing

Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping
A-MPDU with A-MSDU
Basic Trigger frame in EHT MU PPDU
Beamforming sounding
BSRP Trigger frame
BSS critical update
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Dynamic MU SMPS
EMLSR (Enhanced Multilink Single-Radio)
LDPC Rx
LDPC Tx
Load Balancing in MLO
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA127760



Role: Access Point

Page 5 of 5

Wi-Fi CERTIFIED 7™ (continued)

MCS 10-11 Tx
MCS 12-13 Rx
MCS 12-13 Tx
Multi-link reconfiguration – AP removal
Multi-link reconfiguration – AP restart
Multi-RU
MU-RTS Trigger frame
Operating Mode indication
 Operating Mode Indication for 320 MHz
Static puncturing
STR (Simultaneous Transmit and Receive)
SU-MIMO
Triggered uplink access optimization
UL MU-MIMO
UL OFDMA

Wi-Fi CERTIFIED™ n

A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel
RIFS
Short Guard Interval
STBC

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
Extended 5 GHz Channel Support
LDPC Rx
LDPC Tx
MCS 8 Rx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g