Wi-Fi CERTIFIED® Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA113058

Product Info

Date of Certification	January 10, 2024
Company	Huawei Technologies Co., Ltd.
Product Name	Wireless LAN Access Point
Product Model Variant	AirEngine5761R-11 ver.23.1
Model Number	AirEngine5761R-11
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Network management	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-02
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Spectrum & Regulatory Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED® Certificate
Certification ID: WFA113058

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

Ver.A

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d
802.11h

WMM®

WMM®-Power Save

WPA2™-Enterprise 2018-04

WPA2™-Enterprise 2018-04 (continued)

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods
192-bit security

WPA3™-Personal 2020-02

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Cellular Data aware

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
Beamforming sounding
BSRP Trigger frame

Wi-Fi CERTIFIED 6® (continued)

- Compressed Block Ack Rx (buffer size 256)
- Compressed Block Ack Tx (buffer size 256)
- DL MU-MIMO
- DL OFDMA
- Individual Target Wake Time
- LDPC Rx
- LDPC Tx
- MCS 8-9 Rx
- MCS 8-9 Tx
- MCS 10-11 Rx
- MCS 10-11 Tx
- MU EDCA Parameter Set element
- MU-BAR Trigger frame
- Operating mode subfield in A-Control field
- Operating mode indication
- Operating mode UL MU Rx
- SU beamformer
- SU-MIMO
- TXOP RTS Threshold
- UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

- RTS with BW Signaling
- Extended 5 GHz Channel Support
- A-MPDU with A-MSDU
- DL MU-MIMO
- LDPC Rx
- LDPC Tx
- MCS 8-9 Rx
- Short Guard Interval
- STBC
- SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

- A-MPDU Tx
- OBSS on Extension Channel
- Short Guard Interval
- STBC