



# Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: [www.wi-fi.org/certification/programs](http://www.wi-fi.org/certification/programs)

## Certification ID: WFA129418

### Product Info

<b>Date of Certification</b>	January 9, 2024
<b>Company</b>	Shenzhen SDMC Technology Co., Ltd
<b>Product Name</b>	AX5400 Dual Band WiFi6 GPON Terminal
<b>Product Model Variant</b>	NP5454C
<b>Model Number</b>	NP5454T
<b>Category</b>	Routers
<b>Sub-category</b>	Cable, DSL or Other Broadband Gateway (Integrated Home Access Device)

### Summary of Certifications

CLASSIFICATION	CERTIFICATION
<b>Connectivity</b>	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
<b>Optimization</b>	WMM® Wi-Fi Agile Multiband™
<b>Security</b>	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2022-06
<b>Spectrum &amp; Regulatory Features</b>	Spectrum & Regulatory



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA129418



Role: Access Point

Page 2 of 3

## Wi-Fi Components

### Wi-Fi Component Operating System

Linux, version: 4.19.208

### Wi-Fi Component Firmware

17.10.188.75

### RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	4	4

## Certifications

### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz  
40 MHz Channel Width in 2.4 GHz

### 5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz  
40 MHz Channel Width in 5 GHz  
80 MHz Channel Width in 5 GHz  
160 MHz Channel Width in 5 GHz

### Protected Management Frames

### Spectrum & Regulatory

802.11d  
802.11h

### WMM®

### WPA2™-Personal 2021-01

### WPA3™-Personal 2022-06

### Wi-Fi Agile Multiband™

#### Wi-Fi CERTIFIED 6®

4 antenna support  
A-MPDU with A-MSDU  
Basic Trigger frame in HE MU PPDU  
BSRP Trigger frame  
Compressed Block Ack Rx (buffer size 256)  
Compressed Block Ack Tx (buffer size 256)  
DL MU-MIMO  
DL OFDMA  
Individual Target Wake Time  
LDPC Rx  
LDPC Tx  
MCS 8-9 Rx  
MCS 8-9 Tx  
MCS 10-11 Rx  
MCS 10-11 Tx  
MU EDCA Parameter Set element  
MU-BAR Trigger frame  
MU-RTS Trigger frame  
M-BSSID  
Operating mode indication  
SU beamformer  
SU-MIMO  
TXOP RTS Threshold



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA129418



Role: Access Point

Page 3 of 3

## Wi-Fi CERTIFIED 6® (continued)

UL OFDMA

## Wi-Fi CERTIFIED™ a

## Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU  
DL MU-MIMO  
LDPC Rx  
LDPC Tx  
MCS 8-9 Rx  
Short Guard Interval  
STBC  
SU beamformer

## Wi-Fi CERTIFIED™ b

## Wi-Fi CERTIFIED™ g

## Wi-Fi CERTIFIED™ n

A-MPDU Tx  
OBSS on Extension Channel  
Short Guard Interval  
STBC