



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA113058

Product Info

Date of Certification	April 29, 2024
Company	Huawei Technologies Co., Ltd.
Product Name	Wireless LAN Access Point
Product Model Variant	AirEngine5761R-11 ver.23.1.2
Model Number	AirEngine5761R-11
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2023-12 WPA™-Enterprise WPA™-Personal
Spectrum & Regulatory Features	Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA113058



Role: Access Point

Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

Ver.A

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

WPA2™-Enterprise 2018-04 (continued)

EAP methods

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
192-bit security

Protected Management Frames

WPA3™-Personal 2023-12

Spectrum & Regulatory

802.11d
802.11h

WPA™-Enterprise

WPA™-Personal

WMM®

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Cellular Data aware

WMM®-Power Save

WPA2™-Enterprise 2018-04

Wi-Fi CERTIFIED 6®



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA113058



Role: Access Point

Page 3 of 3

Wi-Fi CERTIFIED 6® (continued)

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
Beamforming sounding
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
Operating Mode indication
SU beamformer
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling
Extended 5 GHz Channel Support
A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC

Wi-Fi CERTIFIED™ ac (continued)

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval
STBC