

Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA82565

Product Info

| Date of Certification | March 5, 2024 |
|-----------------------|-------------------------------|
| Company | Intel |
| Product Name | Intel(R) Wi-Fi 6 AX200 160MHz |
| Product Model Variant | Win 11 - 22.80 - Feb24 |
| Model Number | AX200 |
| Category | Computers & Accessories |
| Sub-category | Internal Adapter |

Summary of Certifications

| CLASSIFICATION | CERTIFICATION |
|----------------|--|
| Access | Wi-Fi Protected Setup™ |
| Connectivity | 2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Direct® Wi-Fi Enhanced Open™ 2021-01 |
| Optimization | WMM® WMM®-Power Save Wi-Fi Agile Multiband™ |
| Security | Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-12 WPA™-Enterprise |



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA82565



| Summary of Certifications (continued) | | Page 2 of 4 |
|---------------------------------------|-----------------------|-------------|
| CLASSIFICATION | CERTIFICATION | |
| Security | WPA™-Personal | |
| Spectrum & Regulatory Features | Spectrum & Regulatory | |



Legacy Power Save Unschedule auto PS

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA82565



| Role: Station Page 3 of | | | age 3 of 4 | |
|--|---|---|--------------|--|
| Wi-Fi Components | | | | |
| Wi-Fi Component Operating System Windows 11 | RF Architecture | | | |
| | Bands Supported | Transmit (Tx) | Receive (Rx) | |
| Wi-Fi Component Firmware | 2.4 GHz | 2 | 2 | |
| 22.80 | 5 GHz | 2 | 2 | |
| Certifications | | | | |
| 2.4 GHz Spectrum Capabilities | WPA2™-Enterpris | WPA2™-Enterprise 2018-04 | | |
| 20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz | EAP methods EAP TLS | | | |
| 5 GHz Spectrum Capabilities | EAP TTLS PEAPv0 | | | |
| 20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz | WPA2™-Personal 2021-01 | | | |
| 80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz | WPA3™-Enterprise 2020-02 | | | |
| | EAP methods | | | |
| Protected Management Frames | EAP TLS EAP TTLS | | | |
| | PEAPv0 | | | |
| Spectrum & Regulatory | 192-bit security | | | |
| 802.11h | | 192-bit security RSA 3K with the TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 cipher suite | | |
| WMM® | Fast Transition OTA on | • | | |
| | Fast Transition OTA on Server Certificate Valida | 1 | nsition mode | |
| WMM®-Power Save | | | | |

WPA3[™]-Personal 2020-12

WPA[™]-Enterprise



Wi-Fi CERTIFIED[™] Certificate Certification ID: WFA82565



Page 4 of 4

Role: Station

WPA[™]-Personal

Wi-Fi Agile Multiband™

Beacon Report Measurement Active Mode Beacon Report Measurement Passive Mode Fast Transition OTA on WPA2-Enterprise

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU Beamforming sounding **BSRP** Trigger frame Compressed Block Ack Rx (buffer size 256) DL Mu PPDU multi-tone DL MU-MIMO HE NDP Individual Target Wake Time LDPC Rx LDPC Tx MCS 8-9 Rx MCS 8-9 Tx MCS 10-11 Rx MCS 10-11 Tx MU EDCA Parameter Set element **MU-BAR Trigger frame MU-RTS** Trigger frame OM Control field Tx OM subfield in A-Control field Operating Mode indication SU beamformee SU-MIMO **UL OFDMA** UL TB PPDU multi-tone

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support A-MPDU with A-MSDU DL MU-MIMO LDPC Rx MCS 8-9 Rx Short Guard Interval STBC LDPC Tx SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx OBSS on Extension Channel Power Management Short Guard Interval STBC

Wi-Fi Direct®

Wi-Fi Enhanced Open™ 2021-01

Wi-Fi Protected Setup™

PIN Pushbutton