Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA119745

Product Info	
Date of Certification	February 19, 2024
Company	Ruijie Networks
Product Name	RG-WS Series WLAN Controller and RG-AP880-AR AP
Product Model Variant	RG-AP880-AR V1.0
Model Number	RG-AP880-AR
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-12

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA119745

Wi-Fi Components

Wi-Fi Component Operating System
Linux

Wi-Fi Component Firmware
ESDK6.5GA

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
5 GHz	4	4

Wi-Fi Component Operating System
Linux

Wi-Fi Component Firmware
ESDK6.5GA

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6®

4 antenna support
A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
DL MU-MIMO
DL OFDMA
Individual Target Wake Time

Wi-Fi CERTIFIED 6® (continued)

LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
Operating mode indication
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED™ n (continued)

A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval
STBC