



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA114027

Product Info

Date of Certification	February 19, 2024
Company	Huawei Device Co., Ltd.
Product Name	Smart Phone
Product Model Variant	NAM-LX9 V4
Model Number	NAM-LX9
Category	Phones
Sub-category	Smartphone

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Direct®
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-02 WPA™-Enterprise WPA™-Personal



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA114027



Summary of Certifications (continued)

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory
Features

Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA114027



Role: Access Point

Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

EMUI

Wi-Fi Component Firmware

HL1NTHM

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

Wi-Fi CERTIFIED™ ac (continued)

STBC

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval
STBC

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2020-02

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

LDPC Tx
MCS 8-9 Rx
Short Guard Interval



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA114027



Role: Station

Page 4 of 5

Wi-Fi Components

Wi-Fi Component Operating System

EMUI

Wi-Fi Component Firmware

HL1NTHM

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11h

WMM®

WMM®-Power Save

Legacy Power Save
Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods
EAP AKA
EAP AKA Prime
EAP SIM
EAP TLS
EAP TTLS
PEAPv0
PEAPv1

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods
EAP AKA
EAP AKA Prime
EAP SIM
EAP TLS
EAP TTLS
PEAPv0
PEAPv1
Server Certificate Validation

WPA3™-Personal 2020-02



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA114027



Role: Station

Page 5 of 5

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Beacon Report Measurement Active Mode

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Beamforming sounding
BSRP Trigger frame
DL Mu PPDU multi-tone
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
Operating Mode indication
SU beamformee
SU-MIMO
UL OFDMA
UL TB PPDU multi-tone

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO

Wi-Fi CERTIFIED™ ac (continued)

LDPC Rx
MCS 8-9 Rx
Short Guard Interval
STBC
LDPC Tx
SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval
STBC

Wi-Fi Direct®

Wi-Fi Protected Setup™

Pushbutton