



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA130057

Product Info

Date of Certification March 8, 2024

Company Fujitsu Client Computing Limited

Product Name M.2 Module / FCZSW11E39889-11be

Product Model Variant A Derivative of original model

Model Number FCZSW11E39889-11be

Category Other

Sub-category Other

Summary of Certifications

CL ASSIFICAT	ION (CERTIFICA	TION

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi QoS Management™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2022-12 WPA3[™]-Personal 2023-12





Certification ID: WFA130057

Summary	of Cer	tificatio	ns (con	tinued)
- Garring y		unioauo		

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory

Spectrum & Regulatory

Features



Certification ID: WFA130057



Role: Station		Pa	age 3 of 5	
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Windows 11	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware 1.0.8.21-89b6e002-fw12fd3c65	2.4 GHz	2	2	
	5 GHz	2	2	
	6 GHz	2		
	0 GHZ	2	2	
Certifications				
2.4 GHz Spectrum Capabilities	Spectrum & Regu	ılatory (continue	d)	
20 MHz Channel Width in 2.4 GHz	802.11d			
40 MHz Channel Width in 2.4 GHz	802.11h			
5 GHz Spectrum Capabilities	WMM®			
20 MHz Channel Width in 5 GHz				
40 MHz Channel Width in 5 GHz	Willing-Power Sa	WMM®-Power Save		
80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	Legacy Power Save			
100 MHZ Chairlei Width in 5 GHZ	Unschedule auto PS			
6 GHz Spectrum Capabilities	WPA2™-Enterpri	se 2018-04		
20 MHz Channel Width in 6 GHz	EAP methods			
40 MHz Channel Width in 6 GHz	EAP TLS			
80 MHz Channel Width in 6 GHz 160 MHz Channel Width in 6 GHz	EAP TTLS PEAPv0			
320 MHz channel width in 6 GHz	I LAI VO			
	WPA2™-Persona	l 2021-01		
Protected Management Frames	WPA3™-Enterpri	so 2022-12		



Certification ID: WFA130057



Role: Station Page 4 of 5

WPA3™-Enterprise 2022-12 (continued)

EAP methods

EAP TLS

EAP TTLS

PEAPv0

192-bit security

192-bit security RSA 3K with the

TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384

cipher suite

Fast Transition OTA on WPA3-Enterprise

Server Certificate Validation

WPA3™-Personal 202<u>3-12</u>

AKM 24

Beacon Protection

Wi-Fi Agile Multiband™

Beacon Report Measurement Active Mode

Beacon Report Measurement Passive Mode

Fast Transition OTA on WPA2-Enterprise

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL MU PPDU multi-tone

HE NDP

LDPC Tx

LDPC Rx

Individual Target Wake Time

Wi-Fi CERTIFIED 6® Release 2 (continued)

MCS 10-11 Rx

MCS 10-11 Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode control field

Operating mode subfield in A-Control field

Operating mode indication

SU beamformee

SU-MIMO

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi 6E

Multiple M-BSSID

Wi-Fi 6 Release 2 features

UL MU-MIMO

UL MU Control

UL Extended Range

Target Wake Time information frames

Broadcast Target Wake Time

Dynamic MU SMPS

M-BSSID control frames

Preamble Puncturing

Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping

A-MPDU with A-MSDU

Beamforming sounding

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)





Certification ID: WFA130057

Role: Station Page 5 of 5

Wi-Fi CERTIFIED 7™ (continued)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

EPCS (Emergency Preparedness Communications Services)

priority access

LDPC Rx

LDPC Tx

Load Balancing in MLO

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx

MCS 12-13 Tx

Multi-link reconfiguration - AP removal

Multi-link reconfiguration - AP restart

Multi-RU

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Wi-Fi CERTIFIED™ ac (continued)

Short Guard Interval

STBC

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Power Management

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2023-12

Wi-Fi QoS Management™

Default DSCP to UP mapping

DSCP QoS Map

Mirrored Stream Classification Service

Stream Classification Service

SCS with QoS characteristics