



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA115016

Product Info

Date of Certification March 6, 2024

Company Robert Bosch GmbH

Product Name Cockpit Solution

Product Model Variant MY24_S_Mem_Upgrade

Model Number GM VCU 1.0-23M

Category Other

Sub-category In-vehicle Network

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 3

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ ac
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Personal 2020-12



Certification ID: WFA115016



Role: Access Point Page 2 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Android S

Wi-Fi Component Firmware

1.0.2.0.3261.4

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

Wi-Fi CERTIFIED 6® (continued)

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

SU-MIMO

TXOP RTS Threshold

Wi-Fi CERTIFIED™ a

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2020-12

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

LDPC Rx

LDPC Tx

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

A-MPDU with A-MSDU

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n





Certification ID: WFA115016



Certification ID: WFA115016



Role: Station Page 4 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Android S

Wi-Fi Component Firmware

1.0.2.0.3261.4

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

WPA2™-Enterprise 2018-04 (continued)

EAP methods

EAP TLS

EAP TTLS

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

WPA2™-Personal 2018-04

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

Passpoint® Release 3

Online Sign Up and Policy provisioning

Online Sign Up using single SSID

Venue Information

Terms and Conditions

Roaming Consortium Selection

ANQP

ANQP-based Neighbor report

Beacon Report Measurement Active Mode

Beacon Report Measurement Passive Mode

BTM Query

Cellular Data capable

Protected Management Frames

WMM®

WPA2™-Enterprise 2018-04

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)





Certification ID: WFA115016

Role: Station Page 5 of 5

Wi-Fi CERTIFIED 6® (continued)

Compressed Block Ack Tx (buffer size 256)

DL Mu PPDU multi-tone

DL MU-MIMO

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

OM Control field Tx

OM subfield in A-Control field

Operating Mode indication

SU beamformee

SU-MIMO

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

STBC

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC

A-MPDU Tx

OBSS on Extension Channel

Power Management

Short Guard Interval