



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

### Certification ID: WFA130454

#### **Product Info**

| Date of Certification | July 10, 2024   |  |
|-----------------------|---|--|
| Company               | Askey Computer Corporation  |  |
| Product Name          | Smart 5G Hub  |  |
| Product Model Variant | HH70C   |  |
| Model Number          | HH70C   |  |
| Category              | Routers   |  |
| Sub-category          | Cable, DSL or Other Broadband Gateway (Integrated Home Access Device) |  |

#### **Summary of Certifications**

| CLASSIFICATION | CERTIFICATION   |
|----------------|---|
| Access         | Wi-Fi Protected Setup™  |
| Connectivity   | 2.4 GHz Spectrum Capabilities<br>5 GHz Spectrum Capabilities<br>6 GHz Spectrum Capabilities<br>Wi-Fi CERTIFIED 6®<br>Wi-Fi CERTIFIED 7™<br>Wi-Fi CERTIFIED™ a<br>Wi-Fi CERTIFIED™ b<br>Wi-Fi CERTIFIED™ b<br>Wi-Fi CERTIFIED™ g<br>Wi-Fi CERTIFIED™ n<br>Wi-Fi Enhanced Open™ 2023-12 |
| Optimization   | WMM®<br>Wi-Fi Agile Multiband™<br>Wi-Fi EasyMesh™   |
| Security       | Protected Management Frames<br>WPA2™-Personal 2021-01<br>WPA3™-Personal 2023-12   |



**Certification ID: WFA130454** 



# Summary of Certifications (continued)Page 2 of 6CLASSIFICATIONCERTIFICATIONSpectrum & Regulatory<br/>FeaturesSpectrum & Regulatory

This certificate was downloaded on 2024-10-30 at 02:02:36 UTC



**Certification ID: WFA130454** 



#### **Role: Access Point** Page 3 of 6 **Wi-Fi Components** Wi-Fi Component Operating System **RF** Architecture Linux Bands Supported Transmit (Tx) Receive (Rx) Wi-Fi Component Firmware 2.4 GHz 4 4 V01 5 GHz 4 4 6 GHz 4 4

#### Certifications

| 2.4 GHz Spectrum Capabilities                                      | Spectrum & Regulatory (continued)                    |
|--|--|
| 20 MHz Channel Width in 2.4 GHz<br>40 MHz Channel Width in 2.4 GHz | 802.11d<br>802.11h                                   |
| 5 GHz Spectrum Capabilities  | WMM®   |
| 20 MHz Channel Width in 5 GHz<br>40 MHz Channel Width in 5 GHz     | WPA2™-Personal 2021-01                               |
| 80 MHz Channel Width in 5 GHz<br>160 MHz Channel Width in 5 GHz    | WPA3™-Personal 2023-12                               |
| 6 GHz Spectrum Capabilities  | AKM 24<br>Beacon Protection                          |
| 20 MHz Channel Width in 6 GHz<br>40 MHz Channel Width in 6 GHz     | Wi-Fi Agile Multiband™                               |
| 80 MHz Channel Width in 6 GHz<br>160 MHz Channel Width in 6 GHz    | Automatically populate BSS Transition candidate list |
| 320 MHz channel width in 6 GHz                                     | Wi-Fi CERTIFIED 6®                                   |
| Protected Management Frames  | 4 antenna support<br>A-MPDU with A-MSDU              |
| Spectrum & Regulatory  | Basic Trigger frame in HE MU PPDU                    |



# Wi-Fi CERTIFIED<sup>™</sup> Certificate Certification ID: WFA130454



#### **Role: Access Point**

#### Page 4 of 6

| Wi-Fi CERTIFIED 6® (continued)            | Wi-Fi CERTIFIED 7™ (continued)   |
|---|--|
| BSRP Trigger frame                        | Dynamic MU SMPS  |
| Co-located BSS                            | EMLSR (Enhanced Multilink Single-Radio)                                  |
| Compressed Block Ack Rx (buffer size 256) | EPCS (Emergency Preparedness Communications Services)<br>priority access |
| Compressed Block Ack Tx (buffer size 256) | LDPC Rx  |
| DL MU-MIMO                                | LDPC TX  |
| DL OFDMA                                  |  |
| Individual Target Wake Time               | Load Balancing in MLO  |
| LDPC Rx                                   | MCS 8-9 Rx   |
| LDPC Tx                                   | MCS 8-9 Tx   |
| MCS 8-9 Rx                                | MCS 10-11 Rx   |
| MCS 8-9 Tx                                | MCS 10-11 Tx   |
| MCS 10-11 Rx                              | MCS 12-13 Rx   |
| MCS 10-11 Tx                              | MCS 12-13 Tx   |
| MU EDCA Parameter Set element             | Multi-link reconfiguration – AP removal                                  |
| MU-BAR Trigger frame                      | Multi-link reconfiguration – AP restart                                  |
| MU-RTS Trigger frame                      | Multi-RU   |
| M-BSSID                                   | MU-RTS Trigger frame   |
| Operating mode indication                 | Operating mode indication  |
| SU beamformer                             | Operating mode indication for 320 MHz                                    |
| SU-MIMO                                   | Static puncturing  |
| TXOP RTS Threshold                        | STR (Simultaneous Transmit and Receive)                                  |
| UL OFDMA                                  | SU-MIMO  |
| Wi-Fi 6E                                  | Triggered uplink access optimization                                     |
|   | UL MU-MIMO   |
|   | UL OFDMA   |

#### Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU BSRP Trigger frame BSS critical update Compressed Block Ack Rx (buffer size 256) Compressed Block Ack Tx (buffer size 252) Compressed Block Ack Rx (buffer size 512) DL MU-MIMO DL OFDMA

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU DL MU-MIMO Extended 5 GHz Channel Support LDPC Rx LDPC Tx



Certification ID: WFA130454



Page 5 of 6

#### **Role: Access Point**

## Wi-Fi CERTIFIED™ ac (continued) MCS 8-9 Rx RTS with BW Signaling Short Guard Interval STBC SU beamformer Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n A-MPDU Tx HT Duplicate Mode **OBSS on Extension Channel** Short Guard Interval STBC Wi-Fi Enhanced Open™ 2023-12 Wi-Fi Protected Setup™ PIN Pushbutton



Certification ID: WFA130454



#### **Role: Controller**

**Wi-Fi Components** 

Wi-Fi Component Operating System

Linux

#### Certifications

Wi-Fi EasyMesh™