



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA129613

Product Info

Date of Certification	March 26, 2024
Company	Askey Computer Corporation
Product Name	Business Wi-Fi Extender
Product Model Variant	Wi-Fi7
Model Number	APM7210D-D323
Category	Routers
Sub-category	Repeater, Extender, Mesh System, Controller

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED 7™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2023-12 WPA™-Personal
Spectrum & Regulatory Features	Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA129613



Role: Access Point

Page 2 of 4

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

01.240226.0203

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d
802.11h

WMM®

WMM®-Power Save

Legacy Power Save

WMM®-Power Save (continued)

Unschedule auto PS

WPA2™-Personal 2021-01

WPA3™-Personal 2023-12

AKM 24
Beacon Protection

WPA™-Personal

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA129613



Role: Access Point

Page 3 of 4

Wi-Fi CERTIFIED 6® (continued)

LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating Mode indication
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU
Basic Trigger frame in EHT MU PPDU
BSRP Trigger frame
BSS critical update
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
Compressed Block Ack Rx (buffer size 512)
Compressed Block Ack Tx (buffer size 512)
DL MU-MIMO
DL OFDMA
Dynamic MU SMPS
EMLSR (Enhanced Multilink Single-Radio)
EPCS (Emergency Preparedness Communications Services) priority access
LDPC Rx
LDPC Tx
Load Balancing in MLO

Wi-Fi CERTIFIED 7™ (continued)

MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MCS 12-13 Rx
MCS 12-13 Tx
Multi-RU
MU-RTS Trigger frame
Operating Mode indication
Static puncturing
STR (Simultaneous Transmit and Receive)
SU-MIMO
Triggered uplink access optimization
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA129613



Role: Access Point

Page 4 of 4

Wi-Fi CERTIFIED™ n (continued)

A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval
STBC

Wi-Fi EasyMesh™

Backhaul Link
 Backhaul in 2.4 GHz
 Backhaul in 5 GHz low band
 Backhaul in 5 GHz high band
 Backhaul over Ethernet
Fronthaul Access Point
 Fronthaul in 2.4 GHz
 Fronthaul in 5 GHz low band
 Fronthaul in 5 GHz high band
Agent-initiated Steering capability
Backhaul onboarding with Pushbutton
Client Capability Query
Traffic separation