



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

**Certification ID: WFA123248** 

## **Product Info**

**Date of Certification** March 29, 2024

Company NXP Semiconductors

Product Name 9098

Product Model Variant 9098-R10.7-G

Model Number 9098

**Category** Other

**Sub-category** Embedded Module

# **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ ac
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Direct®

**Optimization** WMM®

Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Personal 2022-06

Spectrum & Regulatory

**Features** 

Spectrum & Regulatory



Certification ID: WFA123248



Role: Access Point Page 2 of 5

Wi-Fi Components

**Wi-Fi Component Operating System** 

Linux

Wi-Fi Component Firmware

p149.37

**RF Architecture** 

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

#### Certifications

### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

#### **5 GHz Spectrum Capabilities**

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

# Protected Management Frames

# Spectrum & Regulatory

802.11d 802.11h

#### **WMM®**

Max Throughput

WPA2™-Personal 2021-01

# WPA3™-Personal 2022-06

#### Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

SU beamformer

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

SU beamformer





**Certification ID: WFA123248** 

| Role: Access Point   | Page 3 of 5 |
|--|-------------|
| Wi-Fi CERTIFIED™ b   |             |
| Wi-Fi CERTIFIED™ g   |             |
| Wi-Fi CERTIFIED™ n   |             |
| HT Duplicate Mode OBSS on Extension Channel Short Guard Interval A-MPDU Tx |             |
| Wi-Fi Protected Setup™   |             |
| PIN<br>Pushbutton  |             |







Role: Station Page 4 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

p149.37

**RF Architecture** 

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz Wi-Fi Agile Multiband™

WPA3™-Personal 2022-06

ANQP

BTM Query

Cellular Data capable

**5 GHz Spectrum Capabilities** 

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

**Protected Management Frames** 

Spectrum & Regulatory

802.11d

802.11h

**WMM®** 

Max Throughput

WPA2™-Personal 2021-01

A-MPDU with A-MSDU

Wi-Fi CERTIFIED 6®

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL Mu PPDU multi-tone

HE NDP

LDPC Tx

LDPC Rx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame





**Certification ID: WFA123248** 

Role: Station Page 5 of 5

## Wi-Fi CERTIFIED 6® (continued)

MU-RTS Trigger frame

Operating Mode indication

SU beamformee

SU-MIMO

UL OFDMA

UL TB PPDU multi-tone

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

LDPC Tx

SU beamformee

### Wi-Fi CERTIFIED™ b

## Wi-Fi CERTIFIED™ g

#### Wi-Fi CERTIFIED™ n

A-MPDU Tx

**OBSS** on Extension Channel

Power Management

Short Guard Interval

## Wi-Fi Direct®

## Wi-Fi Protected Setup™

PIN

Pushbutton